

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division

Sundry Notices and Reports on Wells

<p>1. Type of Well GAS</p> <p>2. Name of Operator <b>BURLINGTON RESOURCES</b> OIL &amp; GAS COMPANY LP</p> <p>3. Address &amp; Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700</p> <p>4. Location of Well, Footage, Sec., T, R, M 1625'FSL, 1500'FWL, Sec.11, T-29-N, R-7-W, NMPM, Rio Arriba County</p>	<p>API # (assigned by OCD) 30-039-24843</p> <p>5. Lease Number Fee</p> <p>6. State Oil&amp;Gas Lease #</p> <p>7. Lease Name/Unit Name San Juan 29-7 Unit NP</p> <p>8. Well No. 551</p> <p>9. Pool Name or Wildcat Basin Fruitland Coal</p> <p>10. Elevation:</p>
---	--

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

4-30-02 MIRU. SDON.

5-1-02 ND WH. NU BOP. PT BOP. PT BOP. TOO H w/99 jts 2 3/8" tbg. TIH w/4 1/2" cmt retainer, set @ 2850'. Pump 5 bbl wtr down tbg. Attempt to reverse circ. TOO H. TIH to 2850'. Load hole w/wtr. Circ hole clean. PT 4 1/2" csg to 500 psi/10 min, OK. Plug #1: pump 31 sx Class "B" neat cmt inside csg @ 2599-2850' to cover Fruitland perfs, 7" shoe & 4 1/2" lnr top. TOO H w/2438'. Plug #2: pump 77 sx Class "B" neat cmt inside csg @ 2027-2438' to cover Kirtland & Ojo Alamo intervals. TOO H to 875'. Plug #3: pump 29 sx Class "B" neat cmt inside csg @ 720-875' to cover Nacimiento interval. TOO H. Pump 0.5 bbl wtr down tbg. PT bradenhead annulus to 300 psi/5 min, OK. TIH, perf 2 sqz holes @ 281'. Establish circ down csg & out bradenhead. Plug #4: pump 68 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt out csg valve. ND BOP. NU WH. Install dry hole marker w/5 sx Class "B" neat cmt. SDON.

5-2-02 RD. Rig released.

Well plugged and abandoned 5-1-02.

SIGNATURE *Peggy Case* Regulatory Supervisor May 14, 2002

no  
(This space for State Use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date JUL 11 2002