

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK DRILL	5. LEASE NUMBER SF-078424
1b. TYPE OF WELL GAS	6. IF INDIAN, ALL. OR TRIBE NAME
2. OPERATOR EL PASO NATURAL GAS CO. 14538 <i>W. J. Caldwell</i>	7. UNIT AGREEMENT NAME SAN JUAN 29-7 UNIT
3. ADDRESS & PHONE NO. OF OPERATOR P O BOX 4289 FARMINGTON, NM 87499	8. FARM OR LEASE NAME SAN JUAN 29-7 UNIT 7465
4. LOCATION OF WELL 2510' FSL 790' FWL	9. WELL NO. 563
14. DISTANCE IN MILES FROM NEAREST TOWN 4 MILES E. OF NAVAJO CITY	10. FIELD, POOL, OR WILDCAT BASIN FRUITLAND COAL 71629
15. DISTANCE FROM PROPOSED LOCATION 890' TO NEAREST PROPERTY OR LEASE LINE.	11. SEC. T. R. M OR BLK. SEC. 24 T29N R07W NMPM
16. ACRES IN LEASE 2160	12. COUNTY RIO ARRIBA
17. ACRES ASSIGNED TO WELL 320.00	13. STATE NM
18. DISTANCE FROM PROPOSED LOCATION TO NEAREST WELL DR. 2640' COMPL., OR APPLIED FOR ON THIS LEASE.	19. PROPOSED DEPTH 3119' 3669'
20. ROTARY OR CABLE TOOLS ROTARY	21. ELEVATIONS (DF, FT, GR, ETC.) 6238' GL 6231'
22. APPROX. DATE WORK WILL START	
23. PROPOSED CASING AND CEMENTING PROGRAM	

*SEE OPERATIONS PLAN

24. AUTHORIZED BY: *W. J. Caldwell*
REG. DRILLING ENGR.

RECEIVED

NOV 08 1990

OIL CON. DIV.
DIST. 3

DATE 8/8/90

PERMIT NO. _____ APPROVAL DATE _____

APPROVED BY _____ TITLE _____ DATE _____

NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-3.

NMOOD

Submit to Appropriate
District Office
State Lease - 4 copies
Fee Lease - 3 copies

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-102
Revised 1-1-89

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III


1000 Rio Brazos Rd., Aztec, NM 87410

WELL LOCATION AND ACREAGE DEDICATION PLAT

All Distances must be from the outer boundaries of the section

Operator <u>El Paso Natural Gas</u>		Lease <u>San Juan 29-7 Unit (SE-078424)</u>		Well No. <u>563</u>
Unit Letter <u>T</u>	Section <u>24</u>	Township <u>29 North</u>	Range <u>7 West</u>	County <u>Rio Arriba</u>
Actual Footage Location of Well: <u>2510</u> feet from the <u>South</u> line and <u>790</u> feet from the <u>West</u> line				
Ground level elev. <u>6231'</u>	Producing Formation <u>Fruitland Coal</u>	Basin <u>Basin</u>	Dedicated Acreage <u>320</u> Acres	

- Outline the acreage dedicated to the subject well by colored pencil or hatchure marks on the plat below.
- If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
- If more than one lease of different ownership is dedicated to the well, have the interest of all owners been consolidated by commutation, unitization, force-pooling, etc.?
☐ Yes ☐ No If answer is "yes" type of consolidation unitization
If answer is "no" list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.)
No allowable will be assigned to the well until all interests have been consolidated (by commutation, unitization, force-pooling, or otherwise) or until a non-standard unit, eliminating such interest, has been approved by the Division.



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Signature Peggy Bradfield

Printed Name Peggy Bradfield

Position Regulatory Affairs

Company El Paso Natural Gas

Date 10-3-90

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

Date Surveyed 8-30-90

Signature Neale C. Edwards

Professional Seal

NEW MEXICO
6857
6857
REGISTERED LAND SURVEYOR

Certificate No. Neale C. Edwards

Well Name: 563 SAN JUAN 29-7 UNIT
 Sec. 24 T29N R07W
 BASIN FRUITLAND COAL

2510'FSL 790'FWL
 RIO ARRIBA NEW MEXICO
 Elevation 6231'GL

Formation tops: Surface- SAN JOSE

Ojo Alamo- 2185

Kirtland- 2314

Fruitland- 2793

Fruitland Coal Top- 2887

Fruitland Coal Base- 3062

Pictured Cliffs- 3062

Intermediate TD- 2865

Total Depth- 3069

Logging Program: Mud logs from intermediate to total depth.

Mud Program:	Interval	Type	Weight	Visc.	Fl. Loss
	0 - 200	Spud	8.4 - 8.9	40-50	no control
	200 - 2865	Non-dispersed	8.4 - 9.1	30-60	no control
	2865 - 3069	Formation Water	8.4		no control

Casing Program:	Hole Size	Depth Interval	Csg. Size	Weight	Grade
	12 1/4"	0 - 200	9 5/8"	32.3#	H-40
	8 3/4"	0 - 2865	7"	20.0#	K-55
	6 1/4"	2815 - 3069	5 1/2"	15.5#	K-55
Tubing Program:		0 - 3069	2 7/8"	6.5#	J-55

Float Equipment: 9 5/8" surface casing - saw tooth guide shoe. Centralizers will be run in accordance with Onshore Order #2.

7" intermediate casing - guide shoe and self-fill insert float valve. Three centralizers run every other joint above shoe. Run insert float one joint above the guide shoe. Two turbolizing type centralizers - one below and one into the base of the Ojo Alamo @ 2314'. Standard centralizers thereafter every fourth joint up to the base of the surface pipe.

5 1/2" production casing - float shoe on bottom and a pre-drilled liner run to the 7" casing with a minimum 50' overlap. Liner hanger is a double slip grip type.

Wellhead Equipment: 9 5/8" x 7" x 2 7/8" x 11" 3000 psi xmas tree assembly.

Cementing:

9 5/8" surface casing - cement with 160 sacks of class "B" cement with 1/4# flocele/sack and 3% calcium chloride (189 cu ft. of slurry, 200% excess to circulate to surface). WOC 12 hours. Test casing to 600 psi for 30 minutes.

7" intermediate casing - lead with 412 sacks of 65/35 class "B" poz with 6% gel, 2% calcium chloride and 1/2 cu ft. Perlite/sack (10.3 gallons of water/sack) tail with 100 sacks of class "B" with 2% calcium chloride. 914 cu ft. of slurry, 110% excess to circulate to surface. If hole conditions permit, a 600 ft spacer will be run ahead of the cement slurry to avoid mud contamination of the cement. WOC 12 hours. If cement does not circulate to surface, a temperature log will be run after 8 hours to determine TOC.

5 1/2" liner - do not cement.

Delgadita Mesa, New Mexico
7.5' Quadrangle
1985 Provisional Edition
Section 24, T29N, R7W NMPM
Rio Arriba County, New Mexico

GOVERNADOR

ROMINE MESA

CANYON

San

Rafael

San Rafael Spring

Proposed Well Pad

Access Road

DCI-00-18

PETTUS 5790

Figure 1. Vicinity map showing location of proposed well pad and associated cultural resources. (90-DCI-033)

-2-

-2-