

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

5. LAND DESIGNATION AND SERIAL NO.

SF-078423

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 29-7 Unit

8. FARM OR LEASE NAME, WELL NO.

San Juan 29-7 U #57A

9. API WELL NO.

30-039-25567

10. FIELD AND POOL, OR WILDCAT

Blanco MV/Basin DK

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Sec. 11, T-29-N, R-7-W

12. COUNTY OR
PARISH
Rio Arriba

13. STATE
NM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

2. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. REMVR ☐ Other ☐

2. NAME OF OPERATOR

Meridian Oil Inc

3. ADDRESS AND TELEPHONE NO.

PO Box 4289, Farmington, New Mexico 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1850' FNL, 1840' FWL

At top prod. interval reported below

At total depth

RECEIVED
DEC 11 1996

OIL CON. DIV.

14. PERMIT NO. DATE ISSUED

15. DATE SPUDDED 7-6-96 16. DATE T.D. REACHED 7-22-96 17. DATE COMPL. (Ready to prod.) 11-20-96 18. ELEVATIONS (DP, RKB, RT, OR, ETC.)* 6314 GR, 6327 KB 19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 7820 21. PLUG BACK T.D., MD & TVD 22. IF MULTIPLE COMPL., HOW MANY* 2 23. INTERVALS DRILLED BY ROTARY TOOLS 0-7820 CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

4830-5667 Mesaverde

Dualled w/Dakota

26. TYPE ELECTRIC AND OTHER LOGS RUN

AIT-ML-SP-GR, APS-LDS-GR, FMI, CMR

27. WAS WELL CORRED
No

29. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
13 3/8	48#	238	16	418 cu.ft.	
9 5/8	36#	3446	12 1/4	2017 cu.ft.	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	BACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
7	3310	5944	783 cu.ft.		2 3/8	5665	5740
4 1/2	5766	7818	417 cu.ft.				

31. PERFORATION RECORD (Interval, size and number)

4830, 4833, 4906, 4911, 4913, 4915,
4920, 4922, 4924, 4929, 4931, 4938,
4944, 4949, 4958, 4961, 4964, 4967,
4970, 4973, 4976, 4979, 4982, 4985,
4988, 5004, 5006, 5008, 5010, 5050

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
4830-5010	1786 bbl slk wtr, 38,500#sd
5050-5298	2708 bbl slk wtr, 100,000#sd
5340-5667	2331 bbl slk wtr, 100,000#sd

33. PRODUCTION

33.* Continued on back
DATE FIRST PRODUCTION 11-20-96
PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing
WELL STATUS (Producing or shut-in) SI
DATE OF TEST 11-20-96 HOURS TESTED CROCK SIZE PROD'N. FOR TEST PERIOD OIL—BSL. GAS—MCF. WATER—BSL. GAS-OIL RATIO
2594 Pitot Gauge
FLOW, TUBING PRESS. CASING PRESSURE CALCULATED 24-HOUR RATE OIL—BSL. GAS—MCF. WATER—BSL. OIL GRAVITY-API (CORR.)
SI 640 SI 750

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

35. LIST OF ATTACHMENTS

None

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available data.

SIGNED [Signature]

TITLE Regulatory Administrator DATE 11-26-96

*(See Instructions and Spaces for Additional Data on Reverse Side)

NMOCD

GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	2193'	2377'	White, cr-gr ss.	Nacimienta Ojo Alamo	999' 2193'	
Kirtland	2377'	2872'	Gry sh interbedded w/tight, gry, fine-gr ss. Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Kirtland Fruitland	2377' 2872'	
Fruitland	2872'	3166'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	3166'	
Pictured Cliffs	3166'	3323'	White, waxy chalky bentonite	Lewis Huerfanito Bent.	3323' 3877'	
Huerfanito Bentonite*	3877'	4164'	Gry fn grn silty, glauconitic sd stone w/drkc gry shale	Chacara Cliff House	4164' 4904'	
Cliff House	4904'	5014'	ss. Gry, fine-grn, dense slt ss.	Menefee Pt.Lookout	5014' 5335'	
Menefee	5014'	5335'	Med-dark gry, fine gr ss, carb sh & coal	Mancos Gallup	5756' 6660'	
Point Lookout	5335'	5756'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Juana Lopez Greenhorn	7148' 7337'	
Mancos	5756'	6660'	Dark gry carb sh.	Graneros Dakota	7339' 7443'	
Gallup	6660'	7148'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg.interbed sh	Dakota Morrison	7443' 7747'	
Greenhorn	7337'	7399'	Highly calc gry sh w/thin lmst.			
Graneros	7399'	7443'	Dk gry shale, fossil & carb w/pyrite incl.			
Dakota	7443'	7747'	Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks			
*Huerfanito Bentonite is the legal top of Mesa Verde in New Mexico (North of the Chacara line)						