


UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐		7. UNIT AGREEMENT NAME San Juan 29-7 Unir	
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐		8. FARM OR LEASE NAME, WELL NO. San Juan 29-7 U #64B	
2. NAME OF OPERATOR BURLINGTON RESOURCES OIL & GAS COMPANY		9. API WELL NO. 30-039-25649	
3. ADDRESS AND TELEPHONE NO. PO BOX 4289, Farmington, NM 87499 (505) 326-9700		10. FIELD AND POOL, OR WILDCAT Blanco Mesaverde	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements) At surface 1510°FSL, 1640°FEL At top prod. interval reported below At total depth R-10720		11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA J Sec. 11, T-29-N, R-7-W	
14. PERMIT NO.		DATE ISSUED	
12. COUNTY OR PARISH Rio Arriba		13. STATE New Mexico	
15. DATE SPUDDED 5-20-97	16. DATE T.D. REACHED 6-1-97	17. DATE COMPL. (Ready to prod.) 8-5-97	18. ELEVATIONS (DF, RKB, RT, BR, ETC.)* 6391 GR, 6403 KB
20. TOTAL DEPTH, MD & TVD 6352		21. PLUG BACK T.D., MD & TVD	22. IF MULTIPLE COMPL. HOW MANY*
23. INTERVALS DRILLED BY		ROTARY TOOLS CABLE TOOLS	
24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* 5287-6246 Mesaverde		25. WAS DIRECTIONAL SURVEY MADE	
26. TYPE ELECTRIC AND OTHER LOGS RUN CNL-GR, CBL-CCL-GR		27. WAS WELL CORED No	
28. CASING RECORD (Report all strings set in well)			
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE
9 5/8	32.3#	530	12 1/4
7	20#	4043	8 3/4
29. LINER RECORD			
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*
4 1/2	3895	6351	436 cu.ft.
30. TUBING RECORD			
SIZE	DEPTH SET (MD)	PACKER SET (MD)	
2 3/8	6239		
31. PERFORATION RECORD (Interval, size and number)			
5287, 5300, 5315, 5330, 5363, 5380, 5400, 5423, 5434, 5445, 5470, 5484, 5493, 5501, 5509, 5525, 5540, 5546, 5552, 5558, 5564, 5579, 5593, 5600, 5613, 5624, 5637, 5645, 5660, 5683, 5706, 5793, 5838, 5850, 5860, 5870, 5905, 5915, 5930, 5940, 5950, 5965, 5975, 5985, 5995.			
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.			
DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED	
5287-5706		1275 bbl x-link gel, 100,000# 20/40 Ariz sd	
5793-6246		1285 bbl x-link gel, 100,000# 20/40 Ariz sd	
Perforations cont'd on back			
33. PRODUCTION			
DATE FIRST PRODUCTION 8-5-97	PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing		WELL STATUS (Producing or shut-in) SI
DATE OF TEST 8-5-97	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD
FLOW TUBING PRESS. SI 18		CASING PRESSURE SI 872	2300 Pitot Gauge
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold			
35. LIST OF ATTACHMENTS None			
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records			
SIGNED 		TITLE Regulatory Administrator	
DATE 8-20-97		DATE 8-22-1997	

ACCEPTED FOR RECORD

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

37. SUMMARY OF POROUS ZONES (Show all important zones of porosity and contents thereof, cover intervals and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries)

38.

GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	WELL NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	2274'	2486'	White, cr-gr ss.	Ojo Alamo		2274'
Kirtland	2486'	2848'	Gry sh interbedded w/light, gry, fine-gr ss.	Kirtland		2486'
Fruitland	2848'	3748'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland		2848'
Pictured Cliffs	3748'	3856'	Bn-Gry, fine grn, tight ss.	Pic. Cliffs		3748'
Lewis	3856'	4476'	Shale w/siltstone stringers	Lewis		3856'
Huerfanto Bentonite*	4476'	4514'	White, waxy chalky bentonite	Huerfanto Bent.		4476'
Chacra	4514'	5280'	Gry fn grn silty, glauconitic sd stone w/drk gry shale	Chacra		4514'
Cliff House	5280'	5580'	ss. Gry, fine-grn, dense sil ss.	Cliff House		5280'
Menefee	5580'	5830'	Med-dark gry, fine gr ss, carb sh & coal	Menefee		5580'
Point Lookout	5830'	6352'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Pt. Lookout		5830'

Perforations continued:
6007, 6043, 6054, 6070, 6105,
6115, 6167, 6183, 6196, 6220,
6234, 6246

*Huerfanto Bentonite is the legal top of Mesa Verde in New Mexico (North of the Chacra line)