UNITED STATES

DEPARTMENT OF THE INTERIOR

Sului y Noci	ces and Renorms on Wellis.	,	
	ces and Reports on Gells	- N 1	
	070 FATALANCE ON	, NW 5.	Lease Number
. Type of Well GAS	010 1144	6.	SF-078399 If Indian, All. or Tribe Name
GAD			
		7.	Unit Agreement Name
Name of Operator			
RESOURCES ^N OIL	& GAS COMPANY		San Juan 29-7 Unit
		8.	Well Name & Number
3. Address & Phone No. of Operator			San Juan 29-7 U #66
PO Box 4289, Farmington, NM 87499 (505) 326-9700		9.	API Well No. 30-039-25664
4. Location of Well, Footage, Sec., T, R, M 2040'FNL, 2175'FWL, Sec.22, T-29-N, R-7-W, NMPM		10.	Field and Pool
			Blanco MV/Basin DK
F 2779		11.	County and State Rio Arriba Co, NM
NSL-3778			KIO AIIIDA CO, KM
Describe Proposed or Compl	leted Operations		
TIH w/5 jts 9 5 "G" neat cmt w/ 16.5 bbl cmt to	9 2:45 p.m. 4-27-97. Drill to 5/8" 32.3# K-55 ST&C csg, set /3% calcium chloride, 0.25 pp o surface. WOC. NU BOP. PT BO	e 229'. (ps Flocele	Cmtd w/165 sx Class (190 cu.ft.). Circ
TIH w/5 jts 9 5 "G" neat cmt w/	$5/8$ " 32.3# K-55 ST&C csg, set $^\prime$ 3% calcium chloride, 0.25 pp	e 229'. (ps Flocele	Cmtd w/165 sx Class (190 cu.ft.). Circ
TIH w/5 jts 9 5 "G" neat cmt w/ 16.5 bbl cmt to	$5/8$ " 32.3# K-55 ST&C csg, set $^\prime$ 3% calcium chloride, 0.25 pp	e 229'. (ps Flocele	Cmtd w/165 sx Class (190 cu.ft.). Circ
TIH w/5 jts 9 5 "G" neat cmt w/ 16.5 bbl cmt to	$5/8$ " 32.3# K-55 ST&C csg, set $^\prime$ 3% calcium chloride, 0.25 pp	e 229'. (ps Flocele	Cmtd w/165 sx Class (190 cu.ft.). Circ
TIH w/5 jts 9 5 "G" neat cmt w/ 16.5 bbl cmt to	$5/8$ " 32.3# K-55 ST&C csg, set $^\prime$ 3% calcium chloride, 0.25 pp	e 229'. (ps Flocele	Cmtd w/165 sx Class (190 cu.ft.). Circ
TIH w/5 jts 9 5 "G" neat cmt w/ 16.5 bbl cmt to	$5/8$ " 32.3# K-55 ST&C csg, set $^\prime$ 3% calcium chloride, 0.25 pp	e @ 229'. Cos Flocele OF & csg to	Cmtd w/165 sx Class (190 cu.ft.). Circ 5 600 psi/15 min, OK. EIVED - 5 1997
TIH w/5 jts 9 5 "G" neat cmt w/ 16.5 bbl cmt to	$5/8$ " 32.3# K-55 ST&C csg, set $^\prime$ 3% calcium chloride, 0.25 pp	P & csg to MAY	Cmtd w/165 sx Class (190 cu.ft.). Circ 6 600 psi/15 min, OK.
TIH w/5 jts 9 5 "G" neat cmt w/ 16.5 bbl cmt to 4-28-97 Drilling ahead.	$5/8$ " 32.3# K-55 ST&C csg, set $^\prime$ 3% calcium chloride, 0.25 pp	PEOMAN	Cmtd w/165 sx Class (190 cu.ft.). Circ 5 600 psi/15 min, OK. EIVED - 5 1997
TIH w/5 jts 9 5 "G" neat cmt w/ 16.5 bbl cmt to 4-28-97 Drilling ahead. 4. I hereby certify that the	5/8" 32.3# K-55 ST&C csg, set /3% calcium chloride, 0.25 pg o surface. WOC. NU BOP. PT Bo	P & csg to MAY	Cmtd w/165 sx Class (190 cu.ft.). Circ 5 600 psi/15 min, OK. EIVED 5 1997 CASE 3
TIH w/5 jts 9 5 "G" neat cmt w/ 16.5 bbl cmt to 4-28-97 Drilling ahead. 4. I hereby certify that the igned Man Malhul. This space for Federal or State	foregoing is true and corre Title Regulatory Adminis	ct.	Cmtd w/165 sx Class (190 cu.ft.). Circ 5 600 psi/15 min, OK. EIVED 5 1997 CASE 3
TIH w/5 jts 9 5 "G" neat cmt w/ 16.5 bbl cmt to 4-28-97 Drilling ahead.	foregoing is true and corre Title Regulatory Adminis Office use)	ct.	Cmtd w/165 sx Class (190 cu.ft.). Circ of 600 psi/15 min, OK. EIVED - 5 1997 - 5 1997 - 4/29/97

FARMINGTON DISTRICT OFFICE