

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1195' FNL, 2135' FWL, Sec. 33, T-29-N, R-7-W, NMPM

R-10720

5. Lease Number

SF-078503

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 29-7 Unit

8. Well Name & Number

San Juan 29-7 U #97B

9. API Well No.

30-039-25361

10. Field and Pool

Blanco Mesaverde

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☒ Other - Spud

13. Describe Proposed or Completed Operations

6-24-98 MIRU. Spud well @ 8:30 p.m. 6-24-98. Drill to 235'. Circ hole clean. TOOH.

TIH w/9 5/8" 32.3# H-40 ST&C csg, set @ 232'. Pump 15 bbl wtr ahead.

Cmtd w/245 sx Class "G" neat cmt w/3% calcium chloride, 0.25 pps

Celloflake (289 cu ft.). Circ 16 bbl cmt to surface. WOC.

6-25-98 NU BOP. PT BOP & csg to 600 psi/30 min, OK. Drilling ahead.

6-27-98 Drill to intermediate TD @ 3774'. Circ hole clean. TOOH. TIH w/92 jts 7"

20# J-55 ST&C csg, set @ 3763'. Pump 20 bbl wtr, 40 bbl 11# poz, 10 bbl

wtr ahead. Cmtd w/295 sx Class "B" neat cmt w/3% sodium metasilicate,

0.25 pps Cellophane, 7 pps Gilsonite (864 cu.ft.). Tailed w/90 sx Class

"B" 50/50 poz w/2% gel, 2% calcium chloride, 0.25 pps Cellophane, 7 pps

Gilsonite (125 cu.ft.). No cmt to surface. Circ 30 bbl poz to surface.

WOC.

6-28-98 PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.

6-29-98 Drill to TD @ 6086'. Circ hole clean. TOOH.

6-30-98 TIH w/59 jts 4 1/2" 10.5# J-55 ST&C lnr, set @ 6085'. Top of lnr @ 3587'. Pump

10 bbl wtr, 20 bbl chemical wash, 10 bbl wtr ahead. Cmtd w/261 sx Class

"B" 50/50 poz w/2% gel, 0.25 pps Cellophane, 5 pps Gilsonite, 0.4% fluid

loss (347 cu.ft.). Reverse circ 6 bbl cmt to surface. ND BOP. NU WH. RD.

Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 7/6/98

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

ACCEPTED FOR FILING

JUL 08 1998

FARMINGTON DISTRICT OFFICE

BY [Signature]

NMOC