

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
**BURLINGTON
RESOURCES** OIL & GAS COMPANY

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1995' FNL, 370' FEL, Sec. 32, T-29-N, R-7-W, NMPM, Rio Arriba County

API # (assigned by OCD)
30-039-26046

5. Lease Number

6. State Oil&Gas Lease #
B-10037-83

7. Lease Name/Unit Name
San Juan 29-7 Unit

8. Well No.
31B

9. Pool Name or Wildcat
Blanco Mesaverde

10. Elevation:

Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other -

13. Describe Proposed or Completed Operations

2-19-99 Drill to intermediate TD @ 2665'. Circ hole clean. TOOH.

2-20-99 TIH w/64 jts 7" 23# J-55 LT&C csg, set @ 2661'. Cmdt w/250 sx Class "B" neat cmt w/2% Econolite, 10 pps Gilsonite, 0.5 pps Flocele (728 cu.ft.). Tailed w/90 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 10 pps Gilsonite, 0.5 pps Flocele (126 cu.ft.). Displace w/103 bbl wtr. Circ 38 bbl cmt to surface. WOC. PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.

2-22-99 Drill to TD @ 5957'. Circ hole clean. TOOH. TIH w/80 jts 4 1/2" 10.5# J-55 lnr, set @ 5956'. Top of lnr @ 2552'. Cmdt w/375 sx Class "H" neat cmt w/2% gel, 0.25 pps Flocele, 0.02% retardant, 0.4% fluid loss, 5 pps Gilsonite (495 cu.ft.). Reverse circ 24 bbl cmt to surface. WOC. PT lnr to 3000 psi/15 min, OK. ND BOP. NU WH. RD. Rig released.

SIGNATURE  Regulatory Administrator February 24, 1999

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PERDUE

Approved by _____ Title DEPUTY OIL & GAS INSPECTOR, DIST. #3 Date FEB 26 1999