

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

820' FSL, 395' FEL, Sec. 32, T-29-N, R-7-W, NMPM, Rio Arriba County

API # (assigned by OCD)
30-039-26048

5. Lease Number

6. State Oil&Gas Lease #
B-10037-083
7. Lease Name/Unit Name

San Juan 29-7 Unit
Well No.

31C

9. Pool Name or Wildcat
Blanco Mesaverde

10. Elevation:

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

2-25-99 Drill to intermediate TD @ 2752'. Circ hole clean. TOOH. TIH w/66 jts 7" 23# J-55 LT&C csg, set @ 2747'. Cmdt w/239 sx Class "B" neat cmt w/3% Econolite, 0.5 pps Flocele, 10 pps Gilsonite (695 cu.ft.). Tailed w/90 sx Class "B" neat cmt w/2% gel, 2% calcium chloride, 0.5 pps Flocele, 10 pps Gilsonite (127 cu.ft.). Circ 26 bbl cmt to surface. WOC. PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.

2-28-99 Drill to TD @ 6029'. Circ hole clean. TOOH. TIH w/76 jts 4 1/2" 10.5# J-55 ST&C lnr, set @ 6028'. Top of lnr @ 2579'. Pump 52 bbl wtr, 20 bbl mud flush ahead. Cmdt w/368 sx Class "H" 50/50 poz w/2% gel, 0.25 pps Flocele, 0.2% retardant, 0.4% fluid loss, 5 pps Gilsonite (486 cu.ft.). Reverse circ 20 bbl mud flush to surface, no cmt. WOC. PT 4 1/2" lnr to 3000 psi/15 min, OK. ND BOP. NU WH. RD. Rig released.

SIGNATURE

Charlie T. Perrin Regulatory Administrator March 1, 1999

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PERRIN

DEPUTY OIL & GAS INSPECTOR, DIST. #

Approved by

Title

Date

MAR 2 1999