

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
BURLINGTON RESOURCES OIL & GAS COMPANY

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
590' FNL, 2140' FEL, Sec. 17, T-29-N, R-7-W, NMPM
R-10720, R-10987A

5. Lease Number
SF-078423

6. If Indian, All. or Tribe Name

7. Unit Agreement Name
San Juan 29-7 Unit

8. Well Name & Number
San Juan 29-7 U #44C

9. API Well No.
30-039-26051

10. Field and Pool
Blanco Mesaverde

11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input checked="" type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input checked="" type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

It is intended to alter the approved casing depths and cement of the subject well as follows:

Revisions:

Mud Program:

Interval	Type	Weight	Fluid Loss
0-600'	Spud	8.4-9.0	No control
600-2780'	LSND	8.4-9.0	no control
2780-6132'	Air/Mist	n/a	n/a

Casing Program:

Hole Size	Depth Interval	Casing Size	Weight	Grade
12 1/4"	0-600'	9 5/8"	32.3#	H-40
8 3/4"	0-2780'	7"	20.0#	J-55
6 1/4"	2680-6132'	4 1/2"	10.5#	J-55

Cementing Program:

9 5/8" surface casing - 478 sx Class "B" cement with 0.25 pps Flocele and 3% calcium chloride (564 cu.ft. of slurry, 200% excess to circulate to surface).

7" intermediate casing - lead w/246 sx Class "B" cement with 3% sodium metasilicate, 5 pps Gilsonite, 0.5 pps Flocele. Tail with 85 sx Class "B" 50/50 poz with 2% gel, 2% calcium chloride, 5 pps Gilsonite, 0.5 pps Flocele (836 cu.ft. of slurry, 100% excess to circulate to surface).

4 1/2" production liner - cement with 376 sx Class "B" 50/50 poz with 0.25 pps Flocele, 5 pps Gilsonite, 0.4% fluid loss, 2% gel, 0.1% retardant (496 cu.ft., 50% excess to circulate liner).

14. I hereby certify that the foregoing is true and correct.

Signed James W. Spencer Title Regulatory Administrator Date 3/16/99

(This space for Federal or State Office use)

APPROVED BY JS/ Duane W. Spencer

Title Team Lead, Petroleum Management

Date 3/16/99

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(E)

NMCCD