

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

590' FNL, 2140' FEL, Sec. 17, T-29-N, R-7-W, NMPM

R-10720, R-10987A

5. Lease Number
SF-078423

6. If Indian, All. or
Tribe Name

Unit Agreement Name

San Juan 29-7 Unit
Well Name & Number

San Juan 29-7 U #44C

9. API Well No.
30-039-26051

10. Field and Pool
Blanco Mesaverde

11. County and State
Rio Arriba Co, NM

RECEIVED
APR 3 0 1999

OIL CON. DIV.
DIST. 3

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

Type of Action

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other - Spud
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut off
☐ Conversion to Injection

13. Describe Proposed or Completed Operations

- 4-13-99 MIRU. Spud well @ 9:00 p.m. 4-13-99. Drill to 380'.
4-14-99 Circ hole clean. TOOH. TIH w/8 jts 9 5/8" 32.3# H-40 csg, set @ 374'. Pump 20 bbl wtr ahead. Cmdt w/320 sx Class "B" neat cmt w/3% calcium chloride, 0.25 pps Flocele (378 cu.ft.). Displace w/26.5 bbl wtr. Circ 22 bbl cmt to surface. WOC. NU BOP. PT BOP & csg to 600 psi/30 min, OK. Drilling ahead.
4-16-99 Drill to intermediate TD @ 2775'. Circ hole clean. TOOH. TIH w/66 jts 7" 23# J-55 LT&C csg, set @ 2770'. Pump 20 bbl wtr, 20 bbl mud flush, 20 bbl wtr ahead. Cmdt w/242 sx Class "B" neat cmt w/3% Econolite, 10 pps Gilsonite, 0.5 pps Flocele (704 cu.ft.). Tailed w/90 sx Class "B" 50/50 poz w/2% gel, 10 pps Gilsonite, 0.5 pps Flocele, 2% calcium chloride (127 cu.ft.). Circ 20 bbl cmt to surface. WOC. PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.
4-18-99 Drill to TD @ 6132'. Circ hole clean. TOOH.
4-19-99 TIH w/82 jts 4 1/2" 10.5# J-55 ST&C lnr, set @ 6132'. Top of lnr @ 2614'. Pump 20 bbl wtr, 20 bbl chemical wash, 20 bbl wtr ahead. Cmdt w/375 sx Class "H" neat cmt w/2% gel, 0.25 pps Flocele, 0.1% retardant, 0.4% fluid loss, 5 pps Gilsonite (458 cu.ft.). Reverse circ 16 bbl cmt to surface. WOC. PT lnr to 3000 psi/15 min, OK. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed _____ Title Regulatory Administrator Date 4/21/99

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

APR 21 1999

NMOC