

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

145' FNL, 260' FEL, Sec. 21, T-29-N, R-7-W, NMPM

R-10720

99 AUG -2 PM 2:02
5. Lease Number
SF-078424

070 FNL 6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 29-7 Unit

8. Well Name & Number

San Juan 29-7 U #50B

9. API Well No.

30-039-26072

10. Field and Pool

Blanco Mesaverde

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment

Type of Action

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other -
☒ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut off
☐ Conversion to Injection

13. Describe Proposed or Completed Operations

It is intended to alter the approved casing depths and cement of the subject well.

Revisions:

Mud Program:

Interval	Type	Weight	Fluid Loss
0-120'	Spud	8.4-9.0	No control
120-2748'	LSND	8.4-9.0	No control
2748-6003'	Air/Mist	n/a	n/a

Casing Program:

Hole Size	Depth Interval	Casing Size	Weight	Grade
12 1/4"	0-120'	9 5/8"	32.3#	E-40
8 3/4"	0-2748'	7"	20.0#	J-55
6 1/4"	0-6003'	4 1/2"	10.5#	J-55

Cementing Program:

9 5/8" surface casing - 96 sx Class "B" cement with 0.25 pps Flocele and 3% calcium chloride (113 cu.ft. of slurry, 200% excess to circulate to surface).
7" intermediate casing - lead w/228 sx Class "B" cement with 3% sodium metasilicate, 5 pps Gilsonite, 0.5 pps Flocele. Tail with 90 sx Class "B" 50/50 poz w/2% metasilicate, 2% calcium chloride, 0.25 pps Cellophane, 5 pps Kolite (826 cu.ft. of slurry, 100% excess to circulate to surface).
4 1/2" production casing - cement with 305 sx Class "B" 50/50 poz w/2% gel, 0.25 pps Flocele, 5 pps Gilsonite, 0.4% fluid loss, 0.1% retardant (482 cu.ft., 40% excess to circulate liner).

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 7/30/99

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date AUG

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.