

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

## Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

2580' FSL, 100' FWL, Sec. 31, T-29-N, R-7-W, NMPM

R-10987A

**RECEIVED**  
JUL 26 1999

**OIL CON. DIV.**  
DIST. 3

5. Lease Number

SF-078503

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

San Juan 29-7 Unit

8. Well Name & Number

San Juan 29-7 U #96B

9. API Well No.

30-039-26143

10. Field and Pool

Blanco Mesaverde

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment

Type of Action

☐ Abandonment ☒ Change of Plans  
☐ Recompletion ☐ New Construction  
☐ Plugging Back ☐ Non-Routine Fracturing  
☐ Casing Repair ☐ Water Shut off  
☐ Altering Casing ☐ Conversion to Injection  
☒ Other -

13. Describe Proposed or Completed Operations

It is intended to alter the approved casing depths and cement of the well.

Revisions:

Mud Program:

Interval	Type	Weight	Fluid Loss
0-120'	Spud	8.4-9.0	No control
120-2273'	LSND	8.4-9.0	No control
2273-5581'	Air/Mist	n/a	n/a

Casing Program:

Hole Size	Depth Interval	Casing Size	Weight	Grade
12 1/4"	0-120'	9 5/8"	32.3#	H-40
8 3/4"	0-2273'	7"	20.0#	J-55
6 1/4"	0-5581'	4 1/2"	10.5#	J-55

Cementing Program:

9 5/8" surface casing - 96 sx Class "B" cement with 0.25 pps Flocele and 3% calcium chloride (113 cu.ft. of slurry, 200% excess to circulate to surface).  
7" intermediate casing - lead w/190 sx Class "B" cement with 3% sodium metasilicate, 5 pps Gilsonite, 0.5 pps Flocele. Tail with 90 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 5 pps Gilsonite, 0.5 pps Flocele (683 cu.ft. of slurry, 100% excess to circulate to surface).  
4 1/2" production casing - cement with 310 sx Class "B" 50/50 poz w/2% gel, 0.25 pps Flocele, 5 pps Gilsonite, 0.4% fluid loss, 0.1% retardant (490 cu.ft., 50% excess to circulate liner).

14. I hereby certify that the foregoing is true and correct.

Signed Donna Shadwick (LW) Title Regulatory Administrator Date 7/7/99  
no

(This space for Federal or State Office use)

APPROVED BY AS/Duane W. Spencer Title Team Lead, Petroleum Management Date JUL 22 1999

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NAOCD