

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well GAS	API # (assigned by OCD) 30-039-26995
2. Name of Operator <i>BURLINGTON RESOURCES</i> OIL & GAS COMPANY LP	5. Lease Number
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700	6. State Oil&Gas Lease # B-10037-58
4. Location of Well, Footage, Sec., T, R, M 875' FNL, 1820' FWL, Sec.16, T-29-N, R-7-W, NMPM, Rio Arriba County	7. Lease Name/Unit Name San Juan 29-7 Unit
	8. Well No. 181
	9. Pool Name or Wildcat Blanco Pictured Cliffs
	10. Elevation:

Type of Submission	Type of Action
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment <input checked="" type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion <input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back <input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair <input type="checkbox"/> Water Shut off
	<input checked="" type="checkbox"/> Altering Casing <input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -

13. Describe Proposed or Completed Operations

It is intended to alter the approved surface casing depth and cement of the subject well. The new surface casing depth will be a minimum of 120'. This is the result of the meeting with the Bureau of Land Management, Oil Conservation Division and Burlington Resources on 6-24-02.

Revisions:

Mud Program:

Interval	Type	Weight	Fluid Loss
0-120'	Spud	8.4-8.9	No control

Casing Program:

Hole Size	Depth Interval	Casing Size	Weight	Grade
9 7/8"	0-120'	7"	20#	J-55

Cementing Program:

7" surface casing - 27 sx Class a, B Portland Type I, II cement (32 cu.ft. of slurry, bring cement to surface through 3/4" line).

SIGNATURE *Reggie Case* Regulatory Supervisor June 28, 2002

no
(This space for State Use)

Approved by *CSG must be at least 50' into bedrock* Title DEPUTY OIL & GAS INSPECTOR Date JUL - 2 2002