



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 87-078,57-4
Unit 1/2 Sec. 31 and
SW/2 Sec. 30

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Packer Test & Repair</u>	<u>I</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Frithard
Well No. h-C & h-D located 1150 ft. from N line and 790 ft. from E line of sec. 31
SW/4 Sec. 31
(1/4 Sec. and Sec. No.) 29N 8E 109W
(Twp.) (Range) (Meridian)
Blanco Mesquite
(Field) San Juan New Mexico
(County or Subdivision) (State or Territory)
Undesignated P.C.
The elevation of the derrick floor above sea level is 5781 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

After evidence of communication between MW & PC Zones, well killed w/ water, tubing & packer were pulled and hole in tubing opposite perforations in P.C. zone was discovered. A permanent type packer (Halliburton Type C Production) was set at 2280' with Otis side-door choke at 2279 and 1/2" of rubber protected tubing installed 2270 to 2206. Well unloaded and tested for complete shut-off between MW and PC Zones.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be

Company Delhi-Taylor Oil Corporation

Address P. O. Box 1175

Farmington, New Mexico

By [Signature]

Title Dist. Supt.

