NO. OF COPIES RECEIVED	Form C-103
DISTRIBUTION	Supersedes Old C-102 and C-103
SANTA FE NEW METE SIL CONSERVATION POMMISSION	Effective 1-1-65
FILE	
U.S.G.S. JUL 1 4 1980	5a. Indicate Type of Lease
LAND OFFICE	State Federal Fee.
OPERATOR CON. COM.	5, State Oil & Gas Lease No.
DIST 3	, mmmmmm
SUNDRY NOTICES AND REPORTS ON WELL COLOGICAL SURVEY	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO MENALE HT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.")	7. Unit Agreement Name
OIL GAS X OTHER-	/, Ont Agreement Ivalie
WELL WELL OTHER-  2. Name of Operator	8. Farm or Lease Name
· · · · · · · · · · · · · · · · · · ·	
El Paso Natural Gas Company  3. Address of Operator	Hardie A
Box 990, Farmington, New Mexico - 87401	1
4. Location of Well	10. Field and Pool, or Wildcat
	Blanco Mesa Verde
UNIT LETTER N . 990 FEET FROM THE South LINE AND 1850 FEET FROM	TIMICO MESO VEIGE
THE West LINE, SECTION 26 TOWNSHIP 29N RANGE IN 8W NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12, County
6418, CT	San Juan
Check Appropriate Box To Indicate Nature of Notice, Report or Otl	REPORT OF:
NOTICE OF INTENTION TO:	REFORT OF.
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
	PLUG AND ABANDONMENT
	FEOG AND ABANDONMENT
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JQB OTHER	
Squeeze, Case Cement, Perf & S/W Frac X	
VINEA	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.	estimated date of starting any proposed
In order to increase production it is planned to workover and restimil	Late this well in the
following manner:	
Pull tubing, set a drillable bridge plug near the bottoms of the 7" ce	ising and pressure test
to 1000 psi.	
If tubing is stuck, cut off tubing approximately 100' below the 7" case	sing shoe, set a drillable
cement retainer near the bottom of the 7" casing, squeeze the open ha	ole w/approximately 200
sks. of cement.	
Pressure test the 7" casing to 1000 psi.	
Isolate and squeeze cement any leaks. If leaks are squeezed near the	base of the 0.jo Alamo
formation, no additional block squeeze of the 7" annulus is planned.	
If there are no leaks near the base of the Ojo Alamo formation, performance of the Ojo Alamo formation of the Ojo Alamo forma	rate 2 squeeze boles at
the base of the Ojo Alamo formation and bakes block squeeze the 7" as	mulus with approximately
125 sacks of cement.	
·	to ammovimately ESUOT
Clean out if hole conditions permit, otherwise sidetrack and rearill	
Run a full string of 4 1/2" production casing and sufficient amount of	cement to tle into
the 7" casing shoe. Selectively perforate and sand-water frac the Me	esa verde lormation.
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Original Signed By:	
SIGNED L.O. Van Ryan Petroleum Engineer	
The state of the s	
APPROVED BY MUMP Clintol TITLE Sup Post 111	
APPROVED BY (MMM) CUMS TITLE SUP KINS 161	DATE 1-14-69
CONDITIONS OF APPROVAL, IF ANY:	
y	