(May 1963)	UNITE: DEPARTMENT (D STATES OF THE INTER	SUBMIT IN TRIPLICA (Other instructions of verse side)	re- B	orm approved. udget Bureau ESIGNATION AN	No. 42-R1424.	
	GEOLOG	ICAL SURVEY		1	078502	,	
	UNDRY NOTICES A this form for proposals to dril Use "APPLICATION FOR				N, ALLOTTEE O	R TRIBE NAME	
OIL GAS	S 127		OFFIVED	7. UNIT AGI	REEMENT NAME		
. NAME OF OPERATO	OR		/ // // /	8. FARM OR	LEASE NAME		
El Paso Nati	ral Gas Company		HIN 1 1 1971	9. WELL NO	dewart A		
Box 990, Fa	rmington, New Mexi		y Sta Diequifements. 3	6 (0	DWWO)		
LOCATION OF WELL (Report location clearly and in accordance with any Statequirements. 3 See also space 17 below.) At surface					10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde		
990'N, 990'	6			Sec	R., M., OR BLK. EY OR AREA . 24, T-2 1. P. M.	. AND 9-N, R-8-W	
4. PERMIT NO.	15. ELEV.	6953' GL	F, RT, GR, etc.)	12. COUNTY	OR PARISH 1	3. STATE New Mexico	
6.	Check Appropriate		Nature of Notice, Report, o		Jeen 1	New MENCO	
	NOTICE OF INTENTION TO:			SEQUENT REPORT	of :		
TEST WATER SH	UT-OFF PULL OR AL	TER CASING	WATER SHUT-OFF	X	REPAIRING WEL	L	
FRACTURE TREAT	MULTIPLE C	OMPLETE	FRACTURE TREATMENT	X	ALTERING CASIN	₹G	
SHOOT OR ACIDIZ			SHOOTING OR ACIDIZING (Other) Squeez	<u></u>	BANDONMENT*	•	
REPAIR WELL (Other)	CHANGE PLA	.NS	(Note: Report res	ults of multiple o	ompletion on	Well	
7. DESCRIBE PROPOSE proposed work nent to this wo	. If well is directionally drilled	learly state all pertiner d, give subsurface loca	Completion or Recont details, and give pertinent data ations and measured and true ve	ton including out			
5-26-71 Squaretainer at 2 5-30-71 Side at 6090' w/1: 5-31-71 P. B. 5976-82', 60 dropped 8 set tested to 350	eezed open hole w/1 2720', squeezed thru etrack T.D. 6090'. 25 sacks of cement. T.D. 6076'. Perf. 13-22', 6040-46' w/ ts of 16 balls, flushed 0 psi O. K. Perf. 5	50 sacks of cer perforation w/ Ran 189 joints W.O.C. 18 ht 5832-42', 5854 16 SPZ. Frac ed w/4200 gal. 266-80', 5356-	tubing and set cemer ment. Perf. squeeze /125 sacks of cement. 4 1/2", 19.5# KS produrs. -64', 5888-94', 5913 w/46: 70,000# 20/40 water. Pumped brid /70', 5410-24' w/28 S cells, flushed w/3654	oduction cases—19', 5954—sand, 64,5 ging ball to PZ. Frac v	5', set ce ring (6077 -58', 5968 96 gal. w baffle at w/40,0004	") set 3-72', eter, 5485'.	
			4	RC)	
			TO THE PERSON NAMED IN	JUN 1	0 1971		
			P.: - John son, Alba	U.S. GEOLOG	HCAL CHOUM		
3. I hereby certify t	hat the foregoing is true and o	correct		TENNING!	DA TEM	'	
signed Cirl	nai Signed F. H. W.GOD	TITLE	etroleum Engineer	DATE	6-8-71		
(This space for F	'ederal or State office use)						
APPROVED BY _ CONDITIONS OF	APPROVAL, IF ANY:	TITLE		DATE			