

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Santa Fe
Lease No. 078415
Unit Harvey E. Roelofs

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Sept. 8, 1950, 19

Well No. 1 is located 290 ft. from ~~XXXX~~^{NU}_S line and 2310 ft. from ~~XXXX~~^{NE}_W line of sec. 22SW 1/4 NE 1/4 NE 1/4 Sec. 22 29N 8W NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)Largo Canyon San Juan NM
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drill Mesa Verde Test with rotary tools to top of Point Lookout Sand.
Drill Point Lookout sand and complete with cable tools.
Set 300' 13-3/8 OD 48# sals. casing at 300' cemented to surface.
Set 7" OD 20# sals. casing on Point Lookout sand cemented with 300 sacks.
Estimated TD 500 feet.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Byrd-Frost, Inc.Address Box 911Durango, Colo.By H. P. SlagelTitle Dist. Supt.