NO. OF COPIES RECEIVED 3	Form C-103
DISTRIBUTION	Supersedes Old
SANTA FE / NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
FILE /	
U.S.G.S.	5a. Indicate Type of Lease
LAND OFFICE	State Federal Fee.
OPERATOR /	5. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS TO TELL TESTER OF PLUG BACK TO A DIFFERENT TESTERS.	
	7, Unit Agreement Name
OIL CON. COM.	
2. Name of Operator DIST. 3	8, Farm or Lease Name
El Paso Natural Gas Company 3. Address of Operator	Vandewart A
Box 990, Farmington, New Mexico - 87401	9. Well No. 4 (OWWO)
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER B 790 FEET FROM THE North LINE AND 1550 FEET FRO	Rlanco Mesa Verde
THE East LINE, SECTION 13 TOWNSHIP 29N RANGE NMPN	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
(1)	San Juan
Check Appropriate Box To Indicate Nature of Notice, Report or O	ther Data
MARIOE AT MITTHE TO THE STATE OF THE STATE O	T REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JQB	_
OTHER Squeeze, Case Cement, Frac Treat	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE 1103.	g estimated date of starting any proposed
In order to increase production it is planned to workover and restimuted following manner:	late this well in the
Pull tubing, set a drillable bridge plug near the bottom of the 7" ca	sing & pressure test
to 1000 psi.	
If tubing is stuck, cut off tubing approximately 100' below the 7" ca drillable cement retainer near the bottom of the 7" casing, squeeze w/approximately 200 sks. of cement.	sing shoe, set a the open hole
Pressure test the 7" casing to 1000 psi.	
Isolate and squeeze cement any leaks. If leaks are squeezed near the	
formation, no additional block squeeze of the 7" annulus is planned.	
If there are no leaks near the base of the Ojo Alamo formation, perfo the base of the Ojo Alamo formation and block squeeze the 7" annulus 125 sacks of cement.	
Clean out if hole conditions permit, otherwise sidetrack and redrill	to approximately 5550'.
Run a full string of 4 1/2" production casing and sufficient amount o	f coment to tie into
the 7" casing shoe. Selectively perforate and sand-water fracture t 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Original Signed F. H. WOOD TITLE Petroleum Engineer	DATE 10-15-68
APPROVED BY ENUMBLE CONDITIONS OF APPROVAL, IF ANY:	DATE 16-17-68