

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
E-3671-1

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name --
2. Name of Operator Pubco Petroleum Corporation	8. Farm or Lease Name State "Com"
3. Address of Operator P. O. Box 869, Albuquerque, New Mexico 87103	9. Well No. 40
4. Location of Well UNIT LETTER <u>I</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>790</u> FEET FROM THE <u>East</u> LINE, SECTION <u>16</u> TOWNSHIP <u>29N</u> RANGE <u>8W</u> NMPM.	10. Field and Pool, or Wildcat Blanco Pictured Cliffs <i>Est</i>
15. Elevation (Show whether DF, RT, GR, etc.) 6412' GL	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded @ 2:00 P.M. 8/29/72. Ran 3 joints (129.46') 8-5/8", 20#, H-40, 8 rd. casing. Landed @ 141.50'. Cemented with 100 sacks Class "A" 3% CaCl₂. Cement circulated. P.D. @ 8:00 P.M. 8/29/72. Tack-welded collars in four quadrants on bottom two joints. Use thread lock on bottom 2 joints. WOC 12 hours. Tested BOP and casing to 1000 psi for 30 minutes before drilling out.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles W. Sanders TITLE Area Production Manager DATE 9/05/72

Original Signed by Emery G. Arnold
APPROVED BY _____ TITLE SUPERVISOR DIST. #3 DATE SEP 6 1972

CONDITIONS OF APPROVAL, IF ANY: