

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS
2. Name of Operator
BURLINGTON RESOURCES OIL & GAS COMPANY
3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700
4. Location of Well, Footage, Sec., T, R, M
1786' FNL 850' FWL, Sec.18, T-29-N, R-7-W, NMMPM
5. Lease Number
SF-078945
6. If Indian, All. or Tribe Name
7. Unit Agreement Name
San Juan 29-7 Unit
8. Well Name & Number
San Juan 29-7 U#76A
9. API Well No.
30-039-21629
10. Field and Pool
Blanco Mesaverde
11. County and State
Rio Arriba Co, NM

RECEIVED
DEC 24 1998
OIL CON. DIV.
DIST. 3

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

- | | | |
|--|---|--|
| <input checked="" type="checkbox"/> Notice of Intent | <input type="checkbox"/> Abandonment | <input type="checkbox"/> Change of Plans |
| <input type="checkbox"/> Subsequent Report | <input type="checkbox"/> Recompletion | <input type="checkbox"/> New Construction |
| <input type="checkbox"/> Final Abandonment | <input type="checkbox"/> Plugging Back | <input type="checkbox"/> Non-Routine Fracturing |
| | <input type="checkbox"/> Casing Repair | <input type="checkbox"/> Water Shut off |
| | <input type="checkbox"/> Altering Casing | <input type="checkbox"/> Conversion to Injection |
| | <input checked="" type="checkbox"/> Other - | |

13. Describe Proposed or Completed Operations

It is intended to add Lewis pay to the Mesaverde formation of the subject well according to the attached procedure and wellbore diagram.

RECEIVED
DEC 15 PM 1:49
OIL CON. DIV. NM

14. I hereby certify that the foregoing is true and correct.

Signed Duane W. Spencer (JLD) Title Regulatory Administrator Date 12/14/98
TLW

(This space for Federal or State Office use)

APPROVED BY /s/ Duane W. Spencer Title _____ Date DEC 21 1998

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

3

NMOC

1

San Juan 29-7 Unit #76A
Lewis Pay Add Procedure
Unit F, Section 18, T29N, R07W
Lat: 36°- 43.70178'/Long: 107° - 36.92778'

This well is currently completed in the Cliffhouse, Menefee, and Point Lookout intervals. It is intended to add the Lewis interval to this existing Mesaverde producer. The results of this payadd will be compared with a traditional 70Q 20lb linear gel and CO₂ frac in the same vicinity. The Lewis will be completed in a single stage with 200,000 lbs 20/40 sand in a 80-75Q Clearfrac gel.

1. Inspect location and test rig anchors. Comply with all NMOCD, BLM, Forestry & BR rules and regulations. Dig flowback pit or set flowback tank. Haul to location 2 jts 2-7/8" N-80 tubing and 3-400 bbl frac tanks.
2. MIRU. Fill 400 bbl tanks with 2% KCL water. Run fluid tests on water. Filter water based upon stimulation company water analysis. Record and report SI pressures on tubing, casing and bradenhead. Lay blowdown line. Blow well down and kill with 2% KCL water as necessary. ND WH and NU BOP with flow tee and stripping head. Test operation of rams. NU blooie line and 2-7/8" relief line. Redress production wellhead as needed.
3. TOOH with 2-3/8" Mesaverde production string set at 6145'. Visually inspect tubing, note and report any corrosion and/or scale in/on tubing. Replace bad joints as needed.
4. PU and RIH with a 3-7/8" bit, 4-1/2" (10.5 lb/ft) casing scraper on the 2-3/8" tubing. Clean out to PBTD (~6178') with air/mist. TOOH.
5. TIH with 4-1/2", CIBP, packer and 2-3/8" tubing. Set CIBP at 5000'. Release from CIBP. Fill casing with ~175 bbls water. Set packer just above CIBP. Pressure test CIBP to 3600 psi. Bleed off pressure and release packer. PUH to 4800'. Spot 9 bbls 15% HCL across proposed Lewis perforations (4275-4890'). TOOH.

All acid on this well to contain the following additives per 1000 gals.

2 gal	HAI-81M	Corrosion inhibitor
5 gal	FE-1A	Iron Control
5 gal	FE-2A	Iron Control
1 gal	SSO-21	Surfactant
1 gal	ClaSta XP	Clay control

6. NU wireline company. Run GR-CBL-CCL from PBTD to 200' above TOC behind 7" casing. Evaluate CBL. Tie into liner top at 3805' for correlation. Good cement bond must exist from PBTD to 4150' to continue with the procedure.

LEWIS:

7. TIH with 7" packer and 2 joints of 2-7/8" tubing for wellhead isolation. Set packer and pressure test casing to 3000 psi. Bleed off pressure. Release packer and TOOH.
8. NU wireline. Perforate Lewis with 30 holes using select fire HSC guns loaded with Owens HSC-3125 302T 10 gram charges set at 1 SPF (Av. perf diameter - 0.30", Av. pen. - 16.64" in concrete). ND wireline company.

4275', 4290', 4302', 4306', 4316', 4340', 4346', 4353', 4418', 4421', 4425', 4480', 4489', 4494', 4527', 4545', 4550', 4559', 4570', 4604', 4608', 4671', 4688', 4699', 4705', 4710', 4717', 4775', 4784', 4790' (30 holes total)

9. TIH with 4-1/2" packer and 2-3/8" tubing. Set packer at 4175'.
10. Pressure test surface lines to 4600 psi. Hold tailgate safety meeting. Establish an injection rate into perfs with 2% KCL water observing a maximum pressure of 3600 psi. Once pressure has broken back and stabilized, shut pumps down and obtain an ISIP. Continue to breakdown Lewis perforations with 25 bbls 15% HCL. Drop 60 RCN 7/8" 1.3 specific gravity balls evenly spaced. Attempt to ball off to 3600 psi surface pressure. Use the same additives as in Step 6. ND stimulation company.
11. Bleed off pressure. Release packer. Lower packer to 4800' to knock balls off of perforations. TOOH. Stand back 2-3/8" tubing.
12. TIH with 7" packer and 2 jts 2-7/8" tubing for wellhead isolation. Set packer.
13. **Maximum surface treating pressure is 3000 psi.** Fracture stimulate the Lewis with 200,000 lbs 20/40 Arizona sand in 3310 bbls 80-75Q Clearfrac gel at **50 BPM**. Average surface treating pressure will be 2,461. Perforation and casing friction is estimated to be 1,040 Treat per the following schedule:

Stage	Downhole Foam Volume (gals)	Clean Gel Volume (gals)	N2 Volume (MSCF)	Sand Volume (lbs)
Pad	45,000	9,000	557.9	---
0.5 ppg	3,000	600	37.2	1,500
1.0 ppg	3,500	700	32.5	3,500
1.5 ppg	20,000	4,000	185.6	30,000
2.0 ppg	25,000	5,000	231.9	50,000
2.5 ppg	25,000	5,000	231.8	62,500
3.0 ppg	17,500	3,500	162.2	52,500
Flush (100' above top perf)	6,593	1,978	71.5	0
Totals	145,593	29,778	1,511	200,000

Cut rate throughout flush as pressure allows. Record ISIP, 5 minute, 10 minute and 15 minute SIP. RD stimulation company.

14. Flow well back after 30 minutes to 1 hour through a choke manifold. Open well to pit, starting with a 10/64" choke. If minimal sand is being produced, change to a larger choke size (16/64"). If choke plugs off, shut well in and remove obstruction from choke and return to flowback. Continue increasing choke size and cleaning well up until fluid returns are negligible.
15. When pressures allow, release packer and TOOH. LD 2-7/8" tubing and packer.
16. TIH with 3-7/8" bit on 2-3/8" tubing and clean out to CIBP at 5000'. Alternate between natural flow and blow stages for clean up. **When water rates are 5 BPH and flare will burn consistently, obtain a Lewis pitot gauge.** Drill out CIBP at 5000'. Use a 10-12 BPH mist rate while drilling the plug.


San Juan 29-7 Unit #76A
1999 Discretionary Lewis Pay Add

18. Clean out to PBTD at 6178'. **Obtain final Lewis/Cliffhouse/Menefee/Point Lookout pitot gauge.** TOOH.
19. TIH with an expendable check, one 2-3/8" joint, standard SN and remaining 2-3/8" tubing. Broach tubing while running in hole. CO with air/mist to PBTD again, if necessary. Land tubing at 6145'. ND BOP. NU WH. Pump off expendable check. RDMO. Contact Production Operations for well tie-in.

Recommended:


Production Engineer

Approved:

 12/10/98
Drilling Superintendent

Approved:

 12/8/98
Team Leader

Contact:

Jennifer Dobson

599-4026 (work)

564-3244 (home)

324-2461 (pager)

Unit F, Section 18, T29N, R7W
Rio Arriba County, NM
Lat: 36° - 43.70178'/Long: 107° - 36.92778'

Rio Arriba County, NM

Lat: 36° - 43.70178'/Long: 107° - 36.92778'

Proposed Schematic

