Form 9-331 (May 1963)

*

UNITED STATES SUBMIT IN TRIPLICATE* Other Instructions on reverse side) Form approved. Budget Bureau No. 42-R1424. 5. Least Designation and Aerial No.

GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS' (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)						SF078415A	
						LOTTEE OR TRIBE NAME	
OIL GAS WELL OTHER				LANGE	7. UNIT AGREEM	7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR E1 Dago Natural Cos Cormony				0.1.1076	S. FARM OR LEA	8. FARM OR LEASE NAME	
El Paso Natural Gas Company 3. ADDRESS OF OPERATOR					Roelofs A	9. WELL NO.	
	c 990, Farmingto	on. NM 87	401	and the second	4A		
4. LOCATION O	F WELL (Report location		FFEIL A	State Jeogir Chients.	10. FIELD AND P	POOL, OR WILDCAT	
See also space 17 below.) At surface				Blanco MV	Blanco MV		
i i i i i i i i i i i i i i i i i i i			MAY 25 19	76	Sec. 22,	Sec. 22, T-29-N, R-8-W	
				•		N.M.P.M. 12. COUNTY OR PARISH 13. STATE	
14. PERSITI NO.		6655	(Show whether property of the Control of the Contro	OM. Sy eac.)	San Juan	New Mexico	
16.	Check A	ppropriate Box	To ladicate K	lature of Notice, Report, o	or Other Data		
	NOTICE OF INTE	NTION TO:		SUBS	SEQUENT REPORT OF:		
TEST WAT	ER SHUT-OFF	PULL OR ALTER CA	ASING	WATER SHUT-OFF	X REPAI	IRING WELL	
FRACTURE	TREAT	MULTIPLE COMPLE	TE	FRACTURE TREATMENT		RING CASING	
SHOOT OR		ABANDON*		SHOOTING OR ACIDIZING	ABANI	DONMENT*	
REPAIR WE (Other)	irr []	CHANGE PLANS		(Other) (Note: Report res	ults of multiple complompletion Report and l	letion on Well Log form.)	
proposed	ROPOSED OR COMPLETED OPP work. If well is directi his work.) *	ERATIONS (Clearly onally drilled, give	state all pertinen e subsurface locat	t details, and give pertinent da cions and measured and true ver	ites, including estimat	ed date of starting any	
02-06-76	TD 3649'. Ran 93 joints 7", 23#, N-80 and KE intermediate casing, 3637' set at 3649'. Cemented with 367 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 3000'.						
02-10-76	TD 5904'. Ran 55 joints 4 1/2", 10.23#, API-X52EE casing liner, 2417' set from 3487-5904'. Float collar set at 5887'. Cemented with 420 cu. ft. cement. WOC 18 hours.						
04-14-76	Set 4 1/2" bridge plug at 5887' to isolate casing leak at shoe joint. Ran 7" RTT packer set at 2046' to isolate leak at 2163-2193'. Squeezed under packer with 118 cu. ft. cement. Released packer. WOC 12 hours.						
04-16-76	PBTD 5887'. T 5015', 5047', per zone. Fra sets dropped.	2', 5370' with	h 13 shots				
****	5685', 5745', with 42,000#	5787', 580- 20/40 sand 520 gallon	4', 5824', and 46,00 s water.	5550', 5554', 5582 5875' with 16 shot 0 gallons water. N	s per zone.	Frac'd	
18. I hereby ce	rtify that the foregoing i	s true and correct		Drilling Clerk	DATE	May 13, 1976	
(This space	for Federal or State off	ice use)					
		•			•		
APPROVEI CONDITIO	NS OF APPROVAL, IF A	ANY:	TITLE		DATE		