Form 9-331 (May 1963)			SUBMIT IN TRIPLI (Other instructions verse side)	on re-	Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO. SF 078487B	
S (Do not use	UNDRY NOT this form for propos Use "APPLICA	ICES AND REPORTS rals to drill or to deepen or plus TION FOR PERMIT—" for such	ON WELLS s back to a different reservoir.	1.	3. IF INDIAN, ALLOTT	EZ OR TRIBE NAME
OIL GAN WELL WE	LL LY OTHER				7. UNIT AGREEMENT : 3. FARM OR LEASE N.	
	Petroleum, A	Division of Allied	d Chemical Corpora	tion	Prichard-Fe	
Suite 1122, 1	1860 Lincoln	Street, Denver, Col			2 A	
See also space 1'	7 below.) 6 -29 - 8 _	learly and in accordance with an	MECEIVE		Blanco Mesa	e BLK. AND
NE NW Section	1 33-T31N-R9W	7 (890' FNL, 1740' I	WL) AUG 1 197		Section 3 3	T31N=R9U
14. PERMIT NO.		15. ELEVATIONS (Show whether 6264 GL, 6278	pr. RT., GR., etc.) 4 KB. S. GEOLOGICAL SU	JRVEY _	San Juan	New Mexico
16.	Check Ap	propriate Box To Indicate			ier Dat a	
	NOTICE OF INTEN	TION TO:		SUBSEQUEN	T REPORT OF:	
TEST WATER SE FRACTURE TREA' SHOOT OR ACIDI REPAIR WELL	ze	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	(NOTE: Report	letion results of	multiple completion	CASING X X n on Well
(Other) 17. DESCRIBE PROPOS proposed work nent to this we	 If well is direction 	RATIONS (Clearly state all pertinonally drilled, give subsurface lo	out datails and give pertinen	t dates in	ion Report and Log to cluding estimated d depths for all marks	ate of starting any
Drilled 13-3 Class A cemer held O.K. Drilled 8-3/s sx 65/35 Poz Drilled 6-1/ Cemented w/3 Perforated Pour 48, 5 holes 50,000 gal. Set bridge pour Perforated Couraged	/4" hole to 2 ht. Cement of 4" hole to 33 mix. Cement 8" hole to 54 84 sx 50/50 H boint Lookout 5218-22, 3 ho treated water 1ug at 5085' 40,000 gal. of liffhouse w/3 r and 50,000 bridge plug at lowed 3 hrs.	and cleaned out to at rate of 4449 MC	6# LT&C casing at ce. Tested casing ad 26# K-55 casing d casing to 1000 p D 10.79# X42 liner eat. Cement circu 1 hole 5335, 5 holes 5170-87, 5 holes 5170-87, 5 holes 0,000# sand. Set -80, 4700-98, 4713	g to 10 g at 31 esi for from lated. les 52 es 515 806, 49 bridge 3-20.	88'. Cement 30 min., he 5468' to 298 56-60, 9 hold 52-55, 4966-60 plug at 476 Frac w/55,56 56'. On one	30 min., ted w/420 eld O.K. 84'. les 5240- ted w/ -70, 5036- 60'. 00 gal. e point poten
18. I hereby certify	that the foregoing i) ()d DA	sistant Dist. Prod	l. Mgr.	DATE7	-30-75
(This space for	Federal or State off	ice use)				
APPROVED BY	F APPROVAL, IF	TITLE			DATE	