
Meter Number:89328 Location Name: PRICHARD FEDERAL #2A Location:TN-29 RG-08 SC-06 UL-D

2 - Federal

10CD Zone:OUTSIDE

Hazard Ranking Score:00



### RATIONALE FOR RISK-BASED CLOSURE OF PRODUCTION PITS LOCATED OUTSIDE OF THE VULNERABLE ZONE IN THE SAN JUAN BASIN

This production pit location was ranked according to the criteria in the New Mexico Oil Conservation Division's Unlined Surface Impoundment Closure Guidelines and received a ranking score of zero. The estimated depth to groundwater is greater than 100-feet beneath ground surface (bgs), the pit is not in a well head protection area, and there are no surface water bodies within 1,000 horizontal feet of the pit location.

The primary source, discharge to the pit has been removed. There has been no discharge to the pits for at least 4 years and the pits have been closed for at least one year.

Each pit was backfilled with clean soil and graded in a manner to divert precipitation away from the excavated area. Minimal infiltration of rainfall is expected. Any rainfall that does infiltrate the ground surface must migrate through clean backfill before reaching the residual hydrocarbons.

There is no source material at the ground surface, so direct contact of hydrocarbons with livestock and the populous is not likely.

In general, outside of the vulnerable area and alluvial valleys, bedrock material is generally encountered within 20 feet of the ground surface. Bedrock material in the San Juan Basin consists of interbedded sandstones, shales and clays. According to Freeze and Cherry, 1979, the hydraulic conductivity of the bedrock material are as follows:

 $10^{-9}$  to  $10^{-13}$  cm/sec  $10^{-12}$  to  $10^{-16}$  cm/sec  $10^{-12}$  to  $10^{-15}$  cm/sec Sandstone Shale Clay

Based on this information, the residual hydrocarbons should not migrate to groundwater.

Natural process (bioremediation) are degrading the residual hydrocarbon to carbon dioxide and water and will continue until the source is gone, therefore minimizing any impact to the environment.

Based on the above information, it is highly unlikely that any source material will impact groundwater or ever find an exposure pathway to affect human health and therefore El Paso Field Services Company (EPFS) requests closure of this pit location.

GENERAL	Meter: 89328 Location: PRICHARD FEDERAL #2A  Operator #: 0128 Operator Name: Maridan P/L District: BrownerD  Coordinates: Letter: D Section 6 Township: 29 Range: 8  Or Latitude Longitude  Pit Type: Dehydrator Location Drip: X Line Drip: Other:  Site Assessment Date: 5-11-94 Area: 10 Run: 31							
SITE ASSESSMENT	NMOCD Zone:  (From NMOCD  (From NMOCD  Maps)  Inside  Outside  Outside  (Z)  Indian  Depth to Groundwater  Less Than 50 Feet (20 points)							
KS	Remarks: TWO PITS ONLOCATION. ONE PIT TO BE CLOSED.							
REMARKS	RED LINE + TOPO CONFIRMED LOCATION 13 OUTSIDE V.Z							
RE	DISH IN							
	1 (SP3190) 04/08/94							

# FIELD PIT REMEDIATION/CLOSURE FORM

GENERAL	Meter: 89328 Location: Pridakd Federal # 19  Coordinates: Letter: D_ Section_6 Township: 29 Range: 8  Or Latitude Longitude  Date Started: 6-28-94 Area: 10 Run: 31						
FIELD OBSERVATIONS	Sample Number(s): MK52.  Sample Depth: 4' Feet  Final PID Reading 138 PID Reading Depth 4' Feet  Yes No  Groundwater Encountered (1) (2) Approximate Depth Feet						
CLOSURE	Remediation Method:  Excavation						
REMARKS	Remarks: EPNG lives Marked soil light Gray strong HYDro curben odos Hit sond Stone 4'  Signature of Specialist: Mayor Killian						



# FIELD SERVICES LABORATORY ANALYTICAL REPORT PIT CLOSURE PROJECT - Soil

## SAMPLE IDENTIFICATION

	Field	ID		Lab ID						
SAMPLE NUMBER:	m14 52		945543							
MTR CODE   SITE NAME:	89328		N/A							
SAMPLE DATE   TIME (Hrs):	6-28-9	1	112	22		ı				
SAMPLED BY:				N/A						
DATE OF TPH EXT.   ANAL.:	6-40	94	6/30/94							
DATE OF BTEX EXT.   ANAL.:	NA		time ight Mount Sand Clay							
TYPE   DESCRIPTION: [	TYPE   DESCRIPTION: \( \sqrt{G}		true gui	/)Yorun >a	a/(1011)					
REMARKS:				/		<del></del>				
RESULTS										
PARAMETER	RESULT	UNITS		QUALIFIERS						
			DF	<u> </u>	M(g)	V(mi)				
BENZENE		MG/KG		· · · -						
TOLUENE		MG/KG								
ETHYL BENZENE		MG/KG								
TOTAL XYLENES		MG/KG								
TOTAL BTEX		MG/KG								
TPH (418.1)	1970	MG/KG			1.98	28				
HEADSPACE PID	138	PPM								
PERCENT SOLIDS	P9.2	%				,				
The Surrogate Recovery was at NIA % for this sample All QA/QC was acceptable.  Jarrative:										
OF = Dilution Factor Used Approved By:	Cod On		Date:	7/1/90	′/					

Test Method for Oil and Grease and Petroleum Hydrocarbons in Water and Soil

Perkin-Elmer Model 1600 FT-IR Analysis Report 

74/06/30 14:01

Sample identification 945543

Invitel mass of sample, g

Volume of sample after extraction, ml 72.000

Petroleum hydrocarbons, ppm 1967-937

Met absorbance of hydrocarbons (2900 cm-t)



\*

\*

