Form 9/331 (May 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

GEOLOGICAL SURVEY

Form approved, Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION	AND	SERIAL	NO
SF 078502			

	RY NOTICES AND I			6. IF INDIAN, ALLOTTER OR FRIDE NAME	
OIL GAS X	7. UNIT AGREEMENT NAME				
2. NAME OF OPERATOR	8. FARM OR LEASE NAME				
El Paso Natura	1 Gas Company			Vandewart A	
3. ADDRESS OF OPERATOR				9, WELL NO.	
=-	Farmington, New Mo	exico 87401		1A (PM)	
4. LOCATION OF WELL (Rep See also space 17 below At surface	ort location clearly and in accor	rdance with any Sta	te requirements.*	Blanco Mesa Vorde Blanco P.C. Ext.	
				11. SEC., T., R., M., OR BLK. AND	
800' S	, 800' E			Sec. 11, T-29-N, R-8-W	
14, PERMIT NO.	15. ELEVATIONS	(Show whether DF, RT 6396! GL	, GR, etc.)	San Juan New Mexico	
16.	Check Appropriate Box	To Indicate Nat	ure of Notice, Report, or C	Other Data	
NO	TICE OF INTENTION TO:		SUBSEQ	UENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CAS	SING	WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT	MULTIPLE COMPLET		FRACTURE TREATMENT	ALTERING CASING	
	ABANDON*		SHOOTING OR ACIDIZING	ABANDONMENT*	
SHOOT OR ACIDIZE				- ABANDONNENT	
REPAIR WELL	CHANGE PLANS		(Other)(Note: Report results	of multiple completion on Well	
(Other) 17. DESCRIBE PROPOSED OR C proposed work. If v nent to this work.) *	OMPLETED OPERATIONS (Clearly seel is directionally drilled, give	state all pertinent d subsurface location	etails, and give pertinent dates	letion Report and Log form.) including estimated date of starting any all depths for all markers and zones perti-	
•	3533! Dan 85 id	ninte 711 20	# KS intermediate	casing, 3519' set at	
353	3'. Cemented with utes. Top of cemer	327 cu. ft.			
at	0. 5708'. Ran 72 jo 3366-5708'. Float :18 hours.	oints 4 1/2" collar set	, 10.5#, K-55 casir at 5690'. Cemented	ng liner, 2342' set I with 415 cu. ft. cement.	
315 gal wat 509 gal wat 540 69, gal 557	2-56', 3162-66' with the control of	th 10 SPZ. ed 3 sets of and Menefee with 16 SPZ ed 6 sets of Point Lookou 43-53' with Dropped 6 d Lower Poin 660-65' with	Fraced with 28,000 from 10 balls each. From 4737-50', 4842-58', Fraced with 69,0' from 16 balls each. From 15 5302-16', 5333-42' from 14 SPZ. Fraced with sets of 14 balls each tookout 5488-96', 10 SPZ. Fraced with 10 SPZ.	2. 3102-12', 3126-36', #20/40 sand and 35,050 tushed with 5400 gallons, 4882-91', 5013-21, 5031-39,000#20/40 sand and 74,500 tushed with 6640 gallons 2', 5361-67', 5377-91', th 63,000#20/40 sand and ach. Flushed with 7014, 5507-11', 5551-59', ith 13,300#20/40 sand is each. Sanded off	
18. I hereby certify that the	de foregoing is true and correct				
SIGNED /	1. LIKE 00	TITLEDr	illing Clerk	DATE August 16, 1977	
(This space for Federa	or State office use)	TOYON T		KECEIVED	
CONDITIONS OF APP	ROVAL, IF ANY:	TITLE	100000000	AUG 2 5 1977	

*See Instructions on Reverse Sie

U. S. GEOLOGICAL SURVEY