

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078415

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Roelofs

9. WELL NO.

3 A (PM)

10. FIELD AND POOL, OR WILDCAT

Blanco PC Ext.
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 15, T-29-N, R-8-W
N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
EL PASO NATURAL GAS COMPANY

3. ADDRESS OF OPERATOR
Box 990, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1060'N, 880'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6308'GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☒

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-29-77 T.D. 3300'. Ran 79 joints 7", 20#, K-55 intermediate casing, 3289' set at 3300'. Cemented with 314 cu.ft. cement. W.O.C. 12 hours, held 1200#/30 minutes. Top of cement at 2075'.
7-03-77 T.D. 5595'. Ran 60 joints 4 1/2", 10.5#, K-55 casing liner, 2473' set 3122-5595'. Float collar set at 5578'. Cemented with 433 cu.ft. cement. WOC. 18 hours.
8-22-77 P.B.T.D. 5578'. Tested casing to 3500#, O.K. Perfed Pictured Cliffs 3008-32, 3036-52 W/18 SPZ. Fraced with 40,000# 20/40 sand and 44,220 gallons water. Dropped 1 set of 18 balls each. Flushed with 5200 gallons water. Perfed CH & Men. 4629, 4634, 4656, 4667, 4760, 4766, 4772, 4776, 4780, 4821, 4826, 4880, 4894, 4955, 4976, 5043' W/1 SPZ. Fraced with 42,000# 20/40 sand and 82,700 gallons water. Flushed with 6300 gal water. Perfed P.L. 5132, 5142, 5146, 5172, 5175, 5180, 5184, 5229, 5257, 5264, 5291, 5322, 5392, 5397, 5416, 5478, 5537, 5546, 5559' W/1 SPZ. Fraced with 42,500# 20/40 sand and 84,990 gallons water. Flushed with 7380 gal water.

18. I hereby certify that the foregoing is true and correct

SIGNED

M. P. Dierco

TITLE

Clerk

DATE


Aug. 24, 1977

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE



RECEIVED

DATE

AUG 25 1977

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY