

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 42 R1424

5. LEASE DESIGNATION AND SERIAL NO.

SF 078416A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

HARDIE

9. WELL NO.

1A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 26, T-29-N, R-8-W

N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

EL PASO NATURAL GAS COMPANY

3. ADDRESS OF OPERATOR

BOX 990, FARMINGTON, NEW MEXICO 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1600'S, 1800'E

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, RT, GR, etc.)

6357' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/1/77 T.D. 3289'. Ran 80 joints 7", 20#, K-55 intermediate casing. 3278' set at 3289'. Cemented with 288 cu. ft. cement. W.O.C. 12 hrs, held 1200#/30 minutes. Top of cement at 2200'.

6/4/77 T. D. 5606'. Ran 77 joints 4 1/2", 10.5#, K-55 casing liner, 2503' set 3103-5606'. Float collar set at 5589'. Cemented with 447 cu. ft. cement. W.O.C. 18 hrs.

9/24/77 P.B.T.D. 5589'. Tested casing to 3500#, O.K. Perfed C.H. - Men. 4581-4611, 4623-37, 4651-57, 4694-4718, 4885-94, 4937-45, 4951-59, 4969-80' w/14 SPZ. Fraced with 100,000# 20/40 sand and 100,002 gallons water. Dropped 4 sets of 14 balls each. Flushed with 10,374 gallons water. Perfed upper P.L. 5014-30, 5117-29, 5182-90, 5200-20, 5242-51, 5271-80' w/14 SPZ. Fraced with 75,000# 20/40 sand and 75,012 gallons water. Dropped 5 sets of 14 balls each. Flushed with 6552 gal. water. Perfed lower P.L. 5338-44, 5357-68, 5415-23, 5494-5502, 5524-30, 5540-51' w/10 SPZ. Fraced with 50,000# 20/40 sand and 53,004 gallons water. Dropped 5 sets of 10 balls each. Flushed with 6762 gal. water.

18. I hereby certify that the foregoing is true and correct

SIGNED M. P. Bueco

TITLE Drilling Clerk

DATE 9/28/77

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

SEP 29 1977

*See Instructions on Reverse Side