

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
EL PASO NATURAL GAS CO.
3. ADDRESS OF OPERATOR
BOX 990, FARMINGTON, NEW MEXICO
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 875'S, 1610'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☒
☐
☐
☐
☐
☐
☐

5. LEASE
SF 078046
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Hughes
9. WELL NO.
2A
10. FIELD OR WILDCAT NAME
BLANCO MESA VERDE
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 19, T-29-N, R-8-W
NMPM
12. COUNTY OR PARISH
SAN JUAN
13. STATE
NEW MEXICO
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6482' GL.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/26/78: T.D. 3355'. Ran 82 joints 7", 20#, KS intermediate casing, 3343' set at 3355'. Cemented with 321 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 1800'.

3/30/78: T.D. 5726'. Ran 80 joints 4 1/2", 10.5#, K-55 casing liner, 2529' set 3197-5726'. Float collar set at 5709'. Cemented with 438 cu. ft. cement. WOC 18 hours.

4/12/78: Ran Cement Bond log. Perfed 2 squeeze holes at 4860' and squeezed with 83 cu. ft. cement. WOC. Perfed 2 squeeze holes at 4388' and squeezed w/83 cu. ft. cement. WOC.

4/14/78: PBTD 5709'. Tested casing to 3500#, OK. Perfed Upper and Lower P.L. 5282, 5287, 5292, 5306, 5311, 5316, 5326, 5331, 5336, 5341, 5355, 5364, 5388, 5421, 5437, 5467, 5516, (OVER) Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. B. Busco TITLE Drilling Clerk DATE 4/20/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

