

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-146

5544,5578,5609,5636,5642,5663' w/1 SPZ. Fraced w/70,000# 20/40 sand and 132,000 gallons water. Flushed with 7000 gal. water.
4/15/78: Perfed Menefee 4924-36,4958-66,4977-86,5012-22, 5089-5100,5103-10,5178-90,5196-5208,5232-38' w/12 SPZ. Fraced with 87,000# 20/40 sand and 97,000 gallons water. Dropped 8 sets of 12 balls each. Flushed with 7000 gal. water. Perfed C.H. 4584-88,4656-60,4674-88,4704-24,4737-59,4766-85,4785-4804' w/16 SPZ. Fraced with 98,000# 20/40 sand and 108,000 gallons treated water. Dropped 6 sets of 16 balls each. Flushed with 6500 gal. water.

17. CLOSING TOP OF WELL	14. DATE WELL SITE	13. CLOSING TOP OF WELL	12. CLOSING TOP OF WELL	11. CLOSING TOP OF WELL	10. FIELD OR AREA	9. METHOD OF	8. PLUGS	7. PLUGS	6. PLUGS	5. PLUGS	4. PLUGS	3. PLUGS	2. PLUGS	1. PLUGS
-------------------------	--------------------	-------------------------	-------------------------	-------------------------	-------------------	--------------	----------	----------	----------	----------	----------	----------	----------	----------

1. PLUGS	2. PLUGS	3. PLUGS	4. PLUGS	5. PLUGS	6. PLUGS	7. PLUGS	8. PLUGS	9. METHOD OF	10. FIELD OR AREA	11. CLOSING TOP OF WELL	12. CLOSING TOP OF WELL	13. CLOSING TOP OF WELL	14. DATE WELL SITE	17. CLOSING TOP OF WELL
----------	----------	----------	----------	----------	----------	----------	----------	--------------	-------------------	-------------------------	-------------------------	-------------------------	--------------------	-------------------------

PROPOSED REPORT OF

1. PLUGS

2. PLUGS

3. PLUGS

4. PLUGS

5. PLUGS

6. PLUGS

7. PLUGS

8. PLUGS

9. METHOD OF

10. FIELD OR AREA

11. CLOSING TOP OF WELL

12. CLOSING TOP OF WELL

13. CLOSING TOP OF WELL

14. DATE WELL SITE

17. CLOSING TOP OF WELL