FLOW TEST NO. 2

Tana arabutas Alassa at La

TIME Shour, delej	LAPSED TIME SINCE * *	, PRESEURT		PROD. ZONE	
		Upper Completion	Lewer Completies	TEMP.	REMARKS
	13				
		<u></u>		AND THE PROPERTY AND LESS OF THE PARTY.	
Production rate during test					
Oil:BOPD based onBbls. in				Houn.	Grav GOR
G25: MCFPD: Tested thru (Orifice or Meter):					
Remarks:					
I hereby certify that the information herein contained is true and complete to the best of my knowledge.					
Approved JUN 1 4 1994 Approved					
By Short By Short Title Field					honi Bradshow &
By				TideField Tech	
Title DEPUTY OIL & GAS INSPECTOR, DIST. #3				ate	7-14-94

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following teco appletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrutbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at theur, date) # #

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packet leakage ten shall commence when both sones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one lone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the aumosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in secondance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut in while the zone which was previously shut in is produced.
- 7. Pressures for gas-zone term must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours term: immediately prior to the beguning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day term: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable tert data.

24-hout oil zone tesu: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Aster District Office of the New Mexico Oil Conservation Dirition on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadwright pressures indicated thereon as well as the flowing temperatures (gas 2000s only) and gravity and GOR (oil 2000s only).