

HUGHES LS 002A 1430
 Location - 190-29N-8W
 SINGLE MV
 Orig. Completion - 4/78
 Last File Update - 1/89 by DDM

RECEIVED
 81 M MAIL ROOM
 55 SEP 25 AM 7:38

070 FARMINGTON, NM

BOT OF 9.625 IN OD CSA 211
 36 LB/FT, K-55 CASING
 TOC - SURF

TOP OF 4.5 IN. LINER AT 3197
 BOT OF 7 IN OD CSA 3355, 20 LB/FT
 KS CASING
 TOC - 1800

MV--4SPF PERF 4584-4588
 MV--ISPF PERF 4656-4660
 MV--ISPF PERF 4674-4688
 MV--SPF PERF 4704-4724
 MV--ISPF PERF 4737-4750
 MV--ISPF PERF 4766-4780
 MV--ISPF PERF 4785-4804
 MV--ISPF PERF 4924-4940
 MV--ISPF PERF 4958-4970
 MV--ISPF PERF 5015-5030
 MV--ISPF PERF 5089-5100
 MV--2SPF PERF 5103-5110
 MV--VSPF PERF 5178-5191
 MV--ISPF PERF 5196-5208
 MV--2SPF PERF 5232-5238
 MV--ISPF PERF 5282-5292
 MV--ISPF PERF 5306-5316
 MV--ISPF PERF 5326-5341

5636-

BOT OF 2.375 IN OD TBG AT 5646

PBTD AT 5709 FT.

TOTAL DEPTH 5726 FT.

BOT OF 4.5 IN OD LINER AT 5726
 10.5 LB/FT, K-55 CASING

Cathodic Protection - ?