Location of Well: 0202908

Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #:HUGHES B 003A

Me	ter #:90215	5	RTU	:1-052-11	(County:S	NAUL NA	Í	
	NAME RESE	ERVOIR OR	POOL		TYPE PROD	METHOD	PROD	MEDIUM PROD	
UPR COMP	•				GAS	FLOW		TBG	
LWR COMP				6 GAS		FLOW		TBG	
	- I 	∽ PRI	E-FLO	W SHUT-IN	PRESSURE DA	ATA	1	Wante de Vienne	
	Hour/Date	Shut-In	Len	gth of Time	e Shut-In	SI Pre	ss. PSI	G Stabilzed	
UPR COMP	03/ ≥ /95 &ì		72 h		S	328		yes	
LWR COMP	03/ 2 /95		72 hrs		219		yes		
	.		1	FLOW TEST	DATE NO.1				
c e	nced at (ho	our,date)*				Zon	e Produ	cing (Upr Lwr	
1		LAPSED SINCE			ESSURE Lower	Prod Temp.		REMARKS	
0	3/27/95	Day :	l.	271/280	211		В	oth Zones SI	
0	3/24/95	Day 2	2	322331	217		В	oth Zones SI	
0	3/ 23 /95	Day 3	3	328 331	220			oth Zones SI	
	3/ ३४ /95 ३५	Day 4	1	328 331	219.			W UPPER ZOINE	
	3/ 25 /95	Day !		286 293	220		- 11		
	3/発 /95 ふ し	Day (280 282	221		- 11	44	
	ction rate	BOPD }	oased MFCP		BBLs in neu (Orific	ce or Me	G ter):ME	rav GOR TER	
UPR COMP	Hour, Date	e SI Leng	gth o	f Time SI	SI Press	PSIG	Stabil	ized (yes/no)	
<u> </u>	-							MAR	

(Continue on reverse side)

MANZANARES - 45

COMP

	fe to) 🛡 🛡			NO. 2		
TIME	LAPSED TIME	PRESSURE		Zone producing (Upper or	r Lower's	
flour, delej	IN BINCE # #	Upper Completion	Lawer Completies	PROD. ZONE TEMP,	REMARKS	
	-					
	-					
					And the Thirty Build To the Wall State of the State of th	
duction rate d	luring test					
	ВОРГ) has d ==				
	20.1	> based on	Bols. in _	Hours	Grav GOR	
		MCFP	D: Tested thru ((Orifice or Meter):	GOR	
				• -		
narks:						
narks:						
		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~				
		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		plete to the best of r		
reby centify th	at the informatio	n herein contained	d is true and com	plete to the best of n	ny knowledge.	
reby cenify th	at the informatio	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	d is true and comp	tratorAmo c	ny knowledge. D Production Company	
reby certify the roved	at the informatio	n herein contained	d is true and comp	tratorAmo c	ny knowledge. D Production Company	
reby certify th	at the information Jehnny Rolle Conservation Di	n herein contained vision	d is true and comp	tratorAmo c	ny knowledge. o Production Company our (Bradshaw) 4	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treaument, and whenever remedial work has been done on a well during which the packer or the tubing have been distrurbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shur-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Plow Test No. 1, one lone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced some shall remain shan-in while the some which was previously shut-in is produced.
- 7. Pressures for gas-zone term must be measured on each zone with a deadweight pressure gauge at time intervals as follows: } hours seam immediately prior to the beginning of each flow-period, at fifteen-minute inservals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day term: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil sone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the securacy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil root only, with deadweight pressures as required above being taken on the gas root.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Astec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).