6. IF INDIAN, ALLOTTEE OR TRIBE NAME

5. LEASE

## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

<del></del>	# # # v
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas G	Hughes
well well other	
2. NAME OF OPERATOR	9. WELL NO. 6A
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco M.V.
P.O. Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 21, T-29-N, R-8-W
below.)	N.M.P.M.
AT SURFACE: 1820.9'S, 1600'E	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	San Juan New Mexico
AT TOTAL DEPTH:	
16 CHECK ADDRODDIATE DOV TO INDICATE MATURE OF MOTIOE	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
DECLIFET FOR APPROVAL TO	6381' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
FRACTURE TREAT	보고통화 그 하는 항연원회
SHOOT OR ACIDIZE	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
MULTIPLE COMPLETE	1. 一直连续的一个一块会理的一样。
CHANGE ZONES	ေသ မြောင်းဆို မွာ ၅၆၇ရှိ သို့
ABANDON*	그 그는 그를 하는 유학일 취 그 및 그림의 위험 그녀를 다
(other)	
including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent 2-06-79: TD 3367'. Ran 82 jts. 7", 20#, K-55 in 3367'. Cemented w/361 cu. ft. cement. WOC 12 hoof cement at 2500'.  2-09-79: TD 5705'. Ran 78 jts. 4 1/2", 10.5#, In 5705'. Float collar set 5689'. Cemented w/361 collar set 5689'. Cemented w/361 collar-79: PBTD 5689'. Tested casing to 3500#, Ol 5244,5250,5256,5262,5268,5290,5312,5326,5337,5385592,5611' w/1 SPZ. Fraced w/67,000# 20/40 sand w/7100 gal. water. Perfed C.H. & Men. 4605,4616 4687,4730,4736,4743,4771,4778,4779,4884,4890,4975 Fraced w/72,000# 20/40 sand and 144,000 gal. water. Subsurface Safety Valve: Manu. and Type	to this work.)* Intermediate casing, 3356' set at ours; held 1200#/30 minutes. Top  K-55 casing liner, 2848' set 3221-cu. ft. cement. WOC 18 hours.  K. Perfed P.L5211,5216,5229,5238  1,5406,5455,5467,5502,5530,5541,553  and 134,000 gal. water. Flushed  4622,4628,4635,4658,4664,4670,4673  7,4984,5050,5058,5069' w/1 SPZ.
18. I hereby certify that the foregoing is true and correct	그 그 그 그 이 경우 함께 함께 하는 것이 없다.
M Bull of Desilling Class	rk PATE April 16. 1979
(This space for Federal or State office	re use)
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE
	Section of the control of the contro

NMOCC