

Completion

& NATURAL RESOURCES DEPARTMENTS TO LE CO CY 30 30

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410 | 1505| 334-6178 FAX: (505) 334-6170 nnid_sinte.nm.us/ocd/District III/3distric.htm

> Page 1 Revised 11/16/98

Am Operator 20	NC oco Productio O Amoco Court	n Company		oto e a	RIEAKAGE TES	<i>T</i> Well No <u>.3A</u>					
			·		<u>W</u> API#30-0 <u>145-2</u>						
	NAME OF RESE		F PROD. or Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)						
Upper Completion	Blanco	GA	S	FLOW	TBG						
Lower Completion	Blanco	GA	S	FLOW	TBG						
PRE-FLOW SHUT-IN PRESSURE DATA											
Upper		Hour, date shut-in		shut-in	SI press. Psig	Stabilized? (Yes or No)					
Completion	6/5/ Hour, date shut-in	72 HO		SI press. Psig	YES Stabilized? (Yes or No)						
Lower Completion	6/5/0	72 HO		198	YES						
			FLOW TE	ST NO. 1							
Commenced at (hour, date)*			Zone producing (Upper or Lower):							
TIME (hour,date)	LAPSED TIME SINCE*	PRES	SURE	PROD. ZON TEMP.	E REMARKS						
		Upper Completion	Lower Completion								
6/5	DAY 1	163	197		BOTH ZONES	SHUT IN					
616	DAY 2	เวล	200	BOTH ZONES		HUT IN					
6/7	DAY 3	178	204		BOTH ZONES	BOTH ZONES SHUT IN					
6/8	DAY 4	183	198		FLOW Low	Lower ZONE					
6/9	DAY 5	188	155	FLOW "		ZONE					
6/10	DAY 6	192	152		FLOW "	ZONE					
Production ra	te during test										
Oil:		BOPD based	d on	Bbls. in	HoursGravGOR						
Gas:		MCF	PD; Tested thru	(Orifice or M	leter):						
		MID	-TEST SHUT-IN	PRESSURI	E DATA						
Upper Completion	Hour, date shut-in	Length of time s	shut-in	SI press psig	Stabilized? (Yes or No)						
Lower	Hour, date shut-in	Length of time s	shut-in	SI press. psig	Stabilized? (Yes or No)						

(Continue on reverse side)

FLOW TEST NO. 2

Commence	d at (hour, date)	10		Zone producing (Upper or Lowr):				
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS			
Oil: Gas:			Bbls. D:Tested thru (C		sGravGOR			
hereby certif	y that the inform	nation herein con	tained is true and	d complete to the	bes of my knowledge.	-		
	Servation Division AL SIGNED BY CH				duction Company dshaw	_ New		
3y			Title	Field Tec	h	_		
itleitle	OLL & GAS INSP	ECTOR, DIST.	Date	6-25 <u>-</u>	-01	_		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as woll as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).