

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

30-045-22812

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK  
 DRILL ☒ DEEPEN ☐ PLUG BACK ☐  
 b. TYPE OF WELL  
 OIL WELL ☐ GAS WELL ☒ OTHER ☐  
 SINGLE ZONE ☒ MULTIPLE ZONE ☐  
 2. NAME OF OPERATOR  
 El Paso Natural Gas Company  
 3. ADDRESS OF OPERATOR  
 PO Box 990, Farmington, NM 87401  
 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*)  
 At surface 800'N, 1750'W  
 At proposed prod. zone

5. LEASE DESIGNATION AND SERIAL NO.  
 SF 078416-A  
 6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
 7. UNIT AGREEMENT NAME  
 8. FARM OR LEASE NAME  
 Hardie  
 9. WELL NO.  
 2A  
 10. FIELD AND POOL, OR WILDCAT  
 Blanco Mesa Verde  
 11. SEC., T., R., M., OR BLK.  
 AND SURVEY OR AREA  
 Sec. 25, T-29-N, R-8-W  
 NMPM  
 12. COUNTY OR PARISH  
 San Juan  
 13. STATE  
 NM

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE\*  
 12 miles East of Blanco, NM  
 15. DISTANCE FROM PROPOSED\*  
 LOCATION TO NEAREST  
 PROPERTY OR LEASE LINE, FT.  
 (Also to nearest drlg. unit line, if any)  
 800'  
 16. NO. OF ACRES IN LEASE  
 1600  
 17. NO. OF ACRES ASSIGNED  
 TO THIS WELL  
 320  
 18. DISTANCE FROM PROPOSED LOCATION\*  
 TO NEAREST WELL, DRILLING, COMPLETED,  
 OR APPLIED FOR, ON THIS LEASE, FT.  
 200'  
 19. PROPOSED DEPTH  
 5685'  
 20. ROTARY OR CABLE TOOLS  
 Rotary  
 21. ELEVATIONS (Show whether DF, RT, GR, etc.)  
 6388'GR  
 22. APPROX. DATE WORK WILL START\*

23. PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
13 3/4"	9 5/8"	32.3#	200'	224 cu.ft. to circulate
8 3/4"	7"	20.0#	3390'	304 cu.ft. to cover Ojo Alamo
6 1/4"	4 1/2" liner	10.5#	3240-5685'	431 cu.ft. to fill to 3240'

Selectively perforate and sandwater fracture the Mesa Verde formation.

A 3000 psi WP and 6000 psi test double gate preventer equipped with blind and pipe rams will be used for blow out prevention on this well.

This gas is dedicated.

The W/2 of Section 25 is dedicated to this well.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24. SIGNED N. B. Suess TITLE Drilling Clerk DATE December 8, 197  
 (This space for Federal or State office use)


PERMIT NO. \_\_\_\_\_ APPROVAL DATE \_\_\_\_\_

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
 CONDITIONS OF APPROVAL, IF ANY:

*Okuf*

\*See Instructions On Reverse Side

DEC 12 1977



**NEW MEXICO OIL CONSERVATION COMMISSION**  
**WELL LOCATION AND ACREAGE DEDICATION PLAT**

Form C-102  
 Supersedes C-128  
 Effective 1-1-65

All distances must be from the outer boundaries of the Section.


Operator <b>El Paso Natural Gas Company</b>			Lease <b>Hardie (SF-078416-A)</b>		Well No. <b>2A</b>
Unit Letter <b>C</b>	Section <b>25</b>	Township <b>29N</b>	Range <b>8W</b>	County <b>San Juan</b>	
Actual Postage Location of Well:					
<b>800</b> feet from the <b>North</b> line and		<b>1750</b> feet from the <b>West</b> line			
Ground Level Elev. <b>6388</b>	Producing Formation <b>Mesa Verde</b>	Pool <b>Blanco Mesa Verde</b>		Dedicated Acreage: <b>320.00</b> Acres	

1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

☐ Yes    ☐ No    If answer is "yes," type of consolidation \_\_\_\_\_

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) \_\_\_\_\_

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.



**CERTIFICATION**

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

*A. G. Quico*

Name

Drilling Clerk

Position

El Paso Natural Gas Co.

Company

December 8, 1977

Date

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

Date Surveyed

November 13, 1977

Registered Professional Engineer and/or Land Surveyor

*Fred B. Kern Jr.*  
 Fred B. Kern Jr.

Certificate No.

3950

Multi-Point Surface Use Plan  
Hardie #2A


1. Existing Road - Please refer to Map No. 1 which shows the existing roads. New roads which will be required have been marked on this map. All existing and new roads will be properly maintained during the duration of this project.
2. Planned Access Roads - Please refer to Map No. 1. The grade of the access roads will be consistent with that of the local terrain. The road surface will not exceed twenty feet (20') in width. Upon completion of the project, the access road will be adequately drained to control soil erosion. Drainage facilities may include ditches, water bars, culverts or any other measure deemed necessary by trained Company personnel to insure proper drainage. Gates and/or cattleguards will be installed if necessary.
3. Location of Existing Wells - Please refer to Map No. 2
4. Location of Tank Batteries, Production Facilities, and Production Gathering and Service Lines - Please refer to Maps No. 1 and No. 2. Map No. 2 shows the existing gas gathering lines. Map No. 1 shows the existing roads and new proposed access roads. All known production facilities are shown on these two maps.
5. Location and Type of Water Supply - Water for the proposed project will be obtained from a water hole located in Manzaneras Water Well.
6. Source of Construction Materials - No additional materials will be required to build either the access road or the proposed location.

7. Methods of Handling Waste Materials - All garbage and trash materials will be put into a burn pit shown on the attached Location Plat No. 1. When clean-up operations are begun on the proposed project, the burn pit with its refuse will be buried to a depth of at least three feet (3'). A latrine, the location of which is also shown on Plat No. 1 will be provided for human waste. If large amounts of liquids are left in the reserve pit after completion of the project, the pit will be fenced until the liquids have had adequate time to dry. The location clean-up will not take place until such time as the reserve pit can be properly covered over to prevent run-off from carrying any of these materials into the watershed. No earthen pit will be located on natural drainages; all earthen pits will be so constructed as to prevent leakage from occurring.
8. Ancillary Facilities - No camps or airstrips will be associated with this project.
9. Wellsite Layout - Please refer to the attached Plat No. 1.
10. Plans for Restoration of the Surface - After completion of the proposed project, the location will be cleaned and leveled. The location will be left in such a condition that will enable reseeding operations to be carried out. Seed Mixture #1 will be used. The reseeding operation will be performed during the time period set forth by the regulatory body. The location production equipment will be painted sage gray (#595-36357)
11. Other Information - The terrain is sandstone ledges and high bluffs covered with pinon and cedar. Cattle graze the proposed project site.

12. Operator's Representative - W. D. Dawson, Post Office Box 990,  
Farmington, New Mexico 87401

13. Certification - I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and, that the work associated with the operations proposed herein will be performed by El Paso Natural Gas Company and its contractors and sub-contractors in conformity with this plan and the terms and conditions under which it is approved.

December 8, 1977

  
\_\_\_\_\_  
D. R. Read  
Division Drilling Engineer

DRR:pb

Operations Plan  
Hardie #2A

I. Location: 800'N, 1750'W, Section 25, T-29-N, R-8-W, San Juan County, NM

Field: Blanco Mesa Verde

Elevation: 6388'GL

II. Geology:

A. Formation Tops:	Surface	San Jose	Lewis	3190'
	Ojo Alamo	2055'	Mesa Verde	4675'
	Kirtland	2230'	Menefee	4810'
	Fruitland	2730'	Point Lookout	5233'
	Pic.Cliffs	3065'	Total Depth	5685'

B. Logging Program: GR-Ind. and GR-Density at Total Depth.

C. Coring Program: none

D. Natural Gauges: 4665', 4800', 5225' and at Total Depth.  
Also gauge any noticeable increase in gas. Record all gauges in daily drilling report and on morning report.

III. Drilling:

A. Mud Program: mud from surface to 3390'. Gas from intermediate casing to Total Depth.

IV. Materials:

A. Casing Program:	<u>Hole Size</u>	<u>Depth</u>	<u>Casing Size</u>	<u>Wt.&amp;Grade</u>
	13 3/4"	200'	9 5/8"	32.3# H-40
	8 3/4"	3390'	7"	20.0# K-55
	6 1/4"	3240-5685'	4 1/2"	10.5# K-55

B. Float Equipment: 9 5/8" surface casing - Larkin guide shoe (fig. 102)

7" intermediate casing - Dowell guide shoe (fig. 50101) and Dowell self-fill insert float valve (fig. 53003), 5 B&W stabilizers (Prod. No. 637085) every other joint above shoe. Run float two joints above shoe.

4 1/2" liner - 4 1/2" liner hanger with neoprene packoff. Larkin geyser shoe (fig. 222) and Larkin flapper type float collar (fig. 404 M&F).

C. Tubing: 5685' of 2 3/8", 4.7#, J-55 8rd EUE tubing with a common pump seating nipple above perforated pup joint with bull plugged full joint for mud anchor on bottom.

D. Wellhead Equipment: 10" 900 x 9 5/8" casing head. 10" 900 x 6" 900 xmas tree.


V. Cementing:

9 5/8" surface casing - use 190 sks. of Class "B" cement with 1/4# gel-flake per sack and 3% calcium chloride (224 cu.ft. of slurry, 100% excess to circulate to surface). WOC 12 hours. Test casing to 600#/30 minutes.

7" intermediate casing - use 115 sks. of 65/35 Class "B" Poz with 6% gel and 2% calcium chloride (8.3 gallons of water per sack) followed by 100 sks. of Class "B" with 2% calcium chloride (304 cu.ft. of slurry, 50% excess to cover Ojo Alamo). Run temperature survey at 8 hours. WOC 12 hours. Test casing to 1200#/30 minutes.

4 1/2" liner - precede cement with 20 barrels of gel water (2 sks. gel) Cement with 245 sks. of Class "B" cement with 4% gel, 1/4 cu.ft. of fine gilsonite per sack and 0.6% Halad-9 (431 cu.ft. of slurry, 70% excess to circulate liner). WOC 18 hours.


El Paso Natural Gas Company  
 Typical location plat for Mesa Verde and Abata Wells



NO  
 ↗




# Typical B.O.P. Installation for Mega Verde Well



Series 900 Double Gate BOP, rated  
at 3000 psi Working Pressure  
When gas drilling operations begin a Shaffer type 50  
or equivalent rotating head is installed on top of the  
flow nipple and the flow line is converted into a blowie line

# EL PASO NATURAL GAS COMPANY

Hardi #2A  
NENW 21 -29-8




MAP #1

LEGEND OF SYMBOLS - 1-1-1-1

EXISTING ROADS  
EXISTING FENCE  
EXISTING DRAINAGE  
PROPOSED ROADS  
PROPOSED FENCE  
PROPOSED DRAINAGE

**LLEGIBLE**

T  
29  
N



MAP #2

Proposed Location ●