

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1460'N, 1740'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐	☒
FRACTURE TREAT ☐	☒
SHOOT OR ACIDIZE ☐	☐
REPAIR WELL ☐	☐
PULL OR ALTER CASING ☐	☐
MULTIPLE COMPLETE ☐	☐
CHANGE ZONES ☐	☐
ABANDON* ☐	☐
(other) ☐	☐

5. LEASE
SF 078502A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Roelofs A

9. WELL NO.
2A (PM)

10. FIELD OR WILDCAT NAME
Blanco P.C. & Blanco M.V.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 14, T-29-N, R-8-W
N.M.P.M.

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6345' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-16-79: TD 3357'. Ran 82 jts. 7", 20#, K-55 intermediate casing, 3346' set at 3357'. Cemented w/308 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 2200'.

3-20-79: TD 5696'. Ran 77 jts. 4 1/2", 10.5#, K-55 casing liner, 2483' set 3213-5696'. Float collar set at 5678'. Cemented w/434 cu. ft. cement. WOC 18 hours.

4-02-79: PBTD 5678'. Tested casing to 3500#, OK. Perfed Lower P.L. 5448, 5453, 5467, 5478, 5494, 5518, 5559, 5574, 5578, 5587, 5600, 5604, 5653' w/1 SPZ. Fraced w/29,500# 20/40 sand and 62,500 gal. water. Flushed w/7000 gal. water. Perfed Mass. P.L. 5195, 5203, 5207, 5218, 5225, 5243, 5256, 5262, 5270, 5276, 5281, 5290, 5296, 5302, 5316, 5322, 5335, 5339, 5360, 5367, 5377, 5383, 5389' w/1 SPZ. Fraced w/75,000# 20/40 sand and 150,000 gal. water. Flushed w/6700 gal. water. (OVER)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Drilling Clerk DATE April 4, 1979


(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

nmcc



Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

4-03-79: Perfed C.H. & Men. 4688, 4694, 4709, 4716, 4772, 4778, 4786, 4794, 4803, 4833, 4898, 4930, 4956, 4962, 4969, 4992, 5008, 5023, 5066, 5096, 5104, w/1 SPZ. Fraced w/86,000# 20/40 sand and 172,000 gal. water. Flushed w/6700 gal. water. Perfed P.C. 3036-3048, 3058-3070, 3078-3092, 3101-3118, 3144-3164, w/16-SPZ. Fraced w/75,000# 10/20 sand and 75,000 gal. water. Flushed w/5100 gal. water.

GPO : 1975 O - 214-149

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUMMARY NOTICES AND REPORTS ON WELLS

1. NAME OF WELL	2. LOCATION	3. DATE	4. OPERATOR
5. TYPE OF WELL	6. DEPTH	7. CEMENT PLUG	8. MUD
9. LINER	10. TUBING	11. CLOSING TOP	12. DATE
13. REASON FOR ABANDONMENT	14. DATA ON FORMER OR PRESENT PRODUCTIVE ZONES	15. DATA ON OTHER ZONES WITH PRESENT SIGNIFICANT FLUID CONTENTS	16. DATA ON CEMENT PLUGS
17. DATA ON MUD OR OTHER MATERIAL PLACED BELOW, BETWEEN AND ABOVE PLUGS	18. DATA ON AMOUNT, SIZE, METHOD OF PARTING OF ANY CASING, LINER OR TUBING PULLED	19. DATA ON DEPTH TO TOP OF ANY LEFT IN THE HOLE	20. DATA ON METHOD OF CLOSING TOP OF WELL
21. DATA ON DATE WELL SITE CONDITIONED FOR FINAL INSPECTION	22. DATA ON LOOKING TO APPROVAL OF THE ABANDONMENT	23. DATA ON APPROVAL	24. DATA ON APPROVAL