

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
Tenneco Oil Company
3. ADDRESS OF OPERATOR
720 S. Colo. Blvd., Denver, CO 80222
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2400' FNL & 1560' FEL, Unit G
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Production csg <input type="checkbox"/>	<input checked="" type="checkbox"/>

5. LEASE
USA - SF 078415
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Roelofs
9. WELL NO.
3
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Sec. 9, T-29-N, R-8-W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6463 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/19/79

Spudded 13 3/4" hole on 2/17/79 @ 2:00 p.m., and drilled to 235'. Ran 5 jts of 9 5/8", 36#, K-55 csg set @ 229'. Cemented w/250 Sx class "B" cement w/1% CACL2 & circulated to surface. Tested csg & BOE to 800 psi for 30 min. Reduced hole to 8 3/4" & continued drilling to 3502'. Ran 83 jts of 7", 23#, K-55 csg set @ 3502'. Cemented w/625 Sx 50/50 poz, 6% D-20, followed by 150 Sx class "B" 2% CACL2 cement. WOC 12 hrs. Reduced hole to 6 1/2" and continued drilling.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED Cheryl Tatham TITLE Admin. Supervisor DATE 3/9/79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMO-C