## UNITED STATES

DEPARTMENT OF THE INTERIOR	USA SF-078415
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	<u> </u>
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331-C for such proposals.)	7. UNIT AGREEMENT NAME.
1. oil gas X other	Roelofs है है है है
Well Well Collection	9. WELL NO. 00 00 00 00 00 00 00 00 00 00 00 00 00
2. NAME OF OPERATOR Tenneco 0il Company	
3. ADDRESS OF OPERATOR	Dakota 프로 토스를
720 S. Colorado Blvd., Denver, CO 80222	I II. SEC., I., K., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA ( 합의하다 및 관련하다 Sec 15, T-29-N, R-8-바루하다
AT SURFACE: 790' FSL and 1500' FEL, Unit 0	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	San Juan Sas New Mexico
AT TOTAL DEPTH:	14. API NO. 육통점 표 전환경원
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	6724' GL 출청하고 한 교육으로 기기
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	_ = 1
TEST WATER SHUT-OFF	
FRACTURE TREAT	그 사람은 사람이 가장 살아 되었습니다.
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING [	change on Form 9-330.)
MULTIPLE COMPLETE	
CHANGE ZONES	그 그 그는 사이 그 바로 대한 사람이 있는 것이 없는 것이 없다.
ABANDON* (other) Change Drilling Program	
to use gas rather than mud-laden fluid for	well control state of the second
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
We propose to drill using the following parar	neters
•	
1) Drill 13 3/4" hole to + 300'	0.00
2) Run 9 5/8", 36#, K-55 csg and cement with sufficient cement to circulate	
to surface	### ### ### #########################
3) Drill 8 3/4" hole to + 3500'	
4) Run 7", 23#, K-55 csg and cement with suf	
5) Drill $6\frac{1}{4}$ " hole to T.D. $0 \pm 7940$ ' with gas	S Control of the cont
6) Log well	
7) Run 4½", 10.5#, K-55 to T.D. and 1 stage cement above Mesa Verde zone.	
្នុ 🔪 🥻 ធ្វើកុម្ព័ទ្ធ 👼 🧸 🖫	
Subsurface Safety Valve: Manu. and Type	Set @Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED WALLY TITLE Admin Supervisor DATE 2/28/29	

(This space for Federal or State office Use) J. S.

\*See Instructions on Reverse Site