

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Tenneco Oil Company
3. ADDRESS OF OPERATOR
720 So. Colorado Blvd., Denver, CO. 80222
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 920' FNL & 1800' FEL, Unit B
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- | REQUEST FOR APPROVAL TO: | | SUBSEQUENT REPORT OF: |
|--|--------------------------|--------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | <input type="checkbox"/> |
| (other) Spud & surface, production csg | | |

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/14/79 - 5/18/79

Spudded 13 3/4" hole on 5/11/79 and drilled to 243'. Ran 5 jts 9 5/8", 36#, K-55 csg and set @ 240'. Cemented w/200 Sx class "B" cement w/3% CACL2. Circulated to surface. WOC 12 hrs. NUBOE. Pressure tstd csg to 1000 psi for 30 min-held ok. Reduced hole to 8 3/4" and drilled to 3700'. Ran 83 jts 7", 23#, K-55 csg and set @ 3700'. Cemented w/560 Sx 50/50 poz mix, 4% gel, 6 1/4# Sx Gilsonite, 1/4# Sx Celloflake, followed by 100 Sx class "B" cement, 2% CACL2. WOC 12 hrs. Reduced hole to 6 1/4" and continued drilling.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Curly Statton TITLE Admin. Supervisor DATE 5/25/79

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE

5. LEASE
~~USA~~ SF 078416 A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Wilch
9. WELL NO.
3
10. FIELD OR WILDCAT NAME
Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 23, T-29-N, R-8-W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6712' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

