5. LEASE

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'. Circulated to surface. WOC 12 hour  Subsurface Safety Valve: Manu. and Type  18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Clean Control of This space for Federal or State off	Cemented w/224 cu. ft. cement.  s; held 600#/30 minutes.  Set @ Ft.  April 30, 1979
4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'. Circulated to surface. WOC 12 hour Subsurface Safety Valve: Manu. and Type  18. I hereby certify that the foregoing is true and correct  Drilling Cle	Cemented w/224 cu. ft. cement.  s; held 600#/30 minutes.  Set @ Ft.  April 30, 1979
4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'. Circulated to surface. WOC 12 hour Subsurface Safety Valve: Manu. and Type  18. I hereby certify that the foregoing is true and correct	Cemented w/224 cu. ft. cement.  s; held 600#/30 minutes.  Set @ Ft.
4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'. Circulated to surface. WOC 12 hour	Cemented w/224 cu. ft. cement. es; held 600#/30 minutes.
4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'. Circulated to surface. WOC 12 hour	Cemented w/224 cu. ft. cement. es; held 600#/30 minutes.
4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'.	Cemented w/224 cu. ft. cement.
4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'.	Cemented w/224 cu. ft. cement.
4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'.	Cemented w/224 cu. ft. cement.
4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'.	Cemented w/224 cu. ft. cement.
4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'.	Cemented w/224 cu. ft. cement.
4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'.	Cemented w/224 cu. ft. cement.
4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'.	Cemented w/224 cu. ft. cement.
4-27-79: Spudded well. Drilled surface hole surface casing, 198' set at 209'.	Cemented w/224 cu. ft. cement.
4-27-79: Spudded well. Orilled surface hole	Ran 5 jts. 9 5/8", 36#, K-55
measured and true vertical depths for all markers and zones pertinen	it to this work.)*
<ol> <li>DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d</li> </ol>	
(000-)	
ABANDON*	
CHANGE ZONES	
MULTIPLE COMPLETE	Change on Form 5-330.)
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
SHOOT OR ACIDIZE	
FRACTURE TREAT	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF   X	
DESCRIPTION APPROVAL TO CURRENT PERCENT	6495' GL
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO. 6 1 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico
AT SURFACE: 1700'S, 1480'E AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
below.)	N.M.P.N.
P.O. Box 289, Farmington, New Mexico 87401  4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 30, T-29-N, R-8-W
3. ADDRESS OF OPERATOR	Blanco M.V.
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
2. NAME OF OPERATOR	1A PART HAR
1. oil gas swell other	Bolin 9. WELL NO.
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
IDO HOT 030 THE LOUIS TOT BENEFIT IT THE ST A SABAN OF BIRD DOOR TO B OHICLORY	
(Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS	
(Do not use this form for proposals to drill or to deepen or plug back to a different	6. IF INDIAN, ALLOTTEE OR TRIBE NAME

\*See Instructions on Reverse Side

numbec

U. S. PECKER ON SURVEY