

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 810' FNL, 1795' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other) _____	

SUBSEQUENT REPORT OF:

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/13/82 - MIRUSU. NDWH. NUBOP. Tally & RIH w/l20 jts. tbq.

1/14/82 - Tagged sd fill @ 7680'. Drld. to PBTD 7910'. Pt. csg. to 3500 psi. Circ'd hole w/1% KCL wtr. Spotted 500 gals 7-1/2% DI HCL across perfs. POOH.

1/15/82 - Ran GR/CCL. Perf'd Dakota w/l JSPF, 7655-76', w/2 JSPF 7765-69', 7794-7802', 7851-56' (38' - 55 holes). Acidized & balled off w/1000 gal. 15% wtd. HCL & 86 l.l SG ball slrs. Ball off complete. Rec'd 78 balls, 52 hits. Frac'd Dakota w/60,000 gal. 30# X-L gel & 133,000# 20/40 sd.

1/16/82 - RIH w/tbg. SN & pmp out plug. Tagged sd fill @ 7850'. CO to PBTD w/foam. Killed tbg. Landed same @ 7779'. NDBOP. NUWH. RDMOSU. Kicked well around w/N₂ & left flwg.

1/17/82 - Flwg. to CU.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Aundria Peron TITLE Production Analyst DATE 1/22/82

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

FEB 8 1981

***See Instructions on Reverse Side**

NMOCC

FARMINGTON District

BY