UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF-078416-A
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
	Wilch
1. oil gas	9. WELL NO.
2. NAME OF OPERATOR	1E
Tenneco Oil Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota
Box 3249, Englewood, CO 80155	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
	Sec. 26, T29N, R8W
AT SURFACE: 1765' FSL, 1550' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	San Juan NM
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6339 GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	0333 dik .
TEST WATER SHUT-OFF	part of many 100 miles and the many many many many many many many many
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9-33 day
PULL OR ALTER CASING	UEUEU
CHANGE ZONES	
ABANDON*	C EBUT EX Each Sign
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertine	directionally diffied. Sive appartiace tocations and
$\frac{3/25/83}{2/20/83}$ . NU & test BOP to 1,000 psi.	RIOW hole POOH, log GR/IND 8
-9790703* DASABAA III AT 77911 M ITA DM - 477878	

3/28/83: Reached TD of 7420' @ 1:15 pm, 3/28/83. Blow hole, POOH, log GR/IND & DEN. TIH, LDDP & DC. RU & run 97 jts (4088') 4-1/2" 11.6# & 10.5# K-55 ST&C csg, set @ 7418', LC @ 7374', TOL @ 3318'. Cmt w/285 sx (550 CF) 65:35 POZ + 6% gel + 1/4#/sx celloflake + .6% HL-9, tailed by 150 sx (177 CF) Cl-B + 10% salt + 1/4#/sx celloflake + .6% HL-9. PD @ 3:30 am, 3/29/83, w/1400 psi. Circ 20 bbls wash & trace of cmt to DEN. surface. LDDP, strip cellar, rig released @ 7:00 a.m., 3/29/83.

Subsurface Safety Valve: Manu. and Type	Set @ Ft.	
18. I hereby certify that the foregoing is true and correct  SIGNED	roduction Anabyet April 4, 1983	
(This space for Federal or State office use)		
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	VOCELICA LOU USCOUD	

APR 12 1983

\*See Instructions on Reverse Side

**FARMINGTON DISTRICT**