

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

RECEIVED  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells - 1 PH 2:01

1. Type of Well  
GAS

**RECEIVED**  
MAR - 7 1996

070 FARMINGTON, NM

5. Lease Number  
SF-078487  
6. If Indian, All. or  
Tribe Name  
7. Unit Agreement Name

2. Name of Operator

**MERIDIAN OIL**

**OIL CON. DIV.  
DIST. 3**

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1660' FSL, 1150' FWL, Sec. 4, T-29-N, R-8-W, NMPM

8. Well Name & Number  
Hill #211  
9. API Well No.  
30-045-27011  
10. Field and Pool  
Basin Fruitland Coal  
11. County and State  
San Juan Co, NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

**Type of Submission**

**Type of Action**

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

**13. Describe Proposed or Completed Operations**

2-21-96 MIRU. SDON.

2-22-96 ND WH. NU BOP. TOO H w/98 jts 2 3/8" tbg. TIH w/7" gauge ring to 2950'.  
TOOH. TIH w/7" cmt retainer, set @ 2930'. Circ hole clean w/98 bbl wtr.  
PT csg to 500 psi/5 min, OK. Establish injection. Plug #1: pump 58 sx  
Class "B" cmt below cmt retainer into Fruitland Coal perms, pump 53 sx  
Class "B" cmt on top of cmt retainer, TOC @ 2655'. TOO H to 2275'.  
Plug #2: pump 68 sx Class "B" cmt @ 1922-2275'. TOO H to 872'. SDON.

2-26-96 Load hole w/3 bbl wtr. Plug #3: pump 31 sx Class "B" cmt inside csg @  
711-872'. TOO H. Perf 3 sqz holes @ 274'. Establish circ down csg & out  
bradenhead w/8 bbl wtr. Plug #4: pump 91 sx Class "B" cmt down csg &  
out bradenhead. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH.  
Fill csg w/10 sx Class "B" cmt. Install dry hole marker w/10 sx Class  
"B" cmt.

2-27-96 RD. Rig released. Well plugged and abandoned 2-27-96.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 2/28/96

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

**APPROVED**

MAR 04 1996

DISTRICT MANAGER

NMOCD