

5 1/2" PRODUCTION CASING CEMENT JOB
HUGHES B-18; SUNDRY NOTICE

5 1/2", 17 PPF, K-55, LT & C (FULL STRING)
SHOE DEPTH: 3156'
FLOAT COLLAR DEPTH: 3112'
DV DEPTH: 2330'

1ST STAGE CEMENT

LEAD: 197 FT³ OF CLASS G/PO₂ (35/65) + 6% GEL
+ 10% SALT
+ 0.25% FRICTION REDUCER
+ 6.25 LB/SK GILSONITE
+ 0.25 LB/SK CELLOPHANE FLAKE

TAIL: 94 FT³ OF CLASS G + 2% CaCl₂ + 0.25 LB/SK CELLOPHANE FLAKE

CEMENT TO SURFACE: YES ☐ NO ☒
ESTIMATED TOP OF CEMENT: UNKNOWN

2ND STAGE CEMENT

LEAD: 1062 FT³ OF CLASS G/PO₂ (35/65) + 6% GEL
+ 10% SALT
+ 0.25% FRICTION REDUCER
+ 6.25 LB/SK GILSONITE
+ 0.25 LB/SK CELLOPHANE
FLAKE

TAIL: 80 FT³ OF CLASS G + 2% CaCl₂ + 0.25 LB/SK CELLOPHANE
FLAKE

CEMENT TO SURFACE: YES ☒ NO ☐
ESTIMATED TOP OF CEMENT: SURFACE

Made By RUB

Checked B

Date _____

Page _____ of _____

Conoco Inc.
Calculation Sheet

Title _____

Job No. _____

Field _____

State _____