

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

SG Interests I, Ltd.

3. Address and Telephone No.

P. O. Box 421, Blanco, NM 87412-0421

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1580' FNL & 1450 FEL (Unit Letter G)  
Section 11, T29B, R8W

5. Lease Designation and Serial No.  
SF078502

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Vanderwart A #12

9. API Well No.

30-045-28025

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other

☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection

Production Casing

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Production Casing: TD @ 3217' on 10-08-92

Hole Size: 7 7/8"

Casing 72 Jts 5 1/2", 15.5#, J-55, Casing set @ 3212'  
Guide Shoe @ 3215', Float Collar @ 3166', Centralizers @  
3192', 3150', 3066', 2982', 2898', 2814', 2730', 2646',  
2562', 2478', 2394' & 2310'.

Cement: 225 sx Pacesetter Lite w/1290 gel, 5 pps Hi-Seal, & 1/4 pps  
Cello-Seal (2.92 Yield/657 cu ft) + 100 sx Class B w/190  
CF-14, & 0.490 Thrifty Lite (1.19 Yield/119 cu ft).  
No cement circ to surface - top of cement will be  
determined upon completion when CBL is run.

Did not bump plug.

Plug Down @ 7:15 PM on 10-09-92.

14. I hereby certify that the foregoing is true and correct

Signed Gavin R. Baez

Title Agent (915) 694-6107

Date 10/14/92

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

Date \_\_\_\_\_

NMOCD

OCT 24 1992