

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other Coal Seam

2. Name of Operator
CONOCO INC. Attn: R. R. Heldenbrand

3. Address and Telephone No.
3817 N.W. Expressway, Oklahoma City, OK 73112

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
10 30 11 90
790' FNL & 1590' FEL NW/NE Sec. 17-T29N-R8W

5. Lease Designation and Serial No.
SF-078414

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
DAY "B" #16

9. API Well No.
30-045-28260

10. Field and Pool, or Exploratory Area
Basin Fruitland Coal

11. County or Parish, State
San Juan Co., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other New Spud Well

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on V
Completion or Recompletion Report and Log for

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

See attached Schematic for all Sec. 13 Information

RECEIVED
FEB 9 1991
OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed Ronald R. Heldenbrand
(This space for Federal or State office use)

Title Manager-Regulatory Affairs

Date 1/17/91

Approved by _____
Conditions of approval, if any:

Title _____

ACCEPTED FOR RECORD
Date _____

FEB 1 1991

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

NMOCD

NEW MEXICO SUNDRY NOTICE

DAY B-16

SPUD @ 1600 HRS; 12-1-90

RIG RELEASED @ 1800 HRS; 12-17-90

200 SX (230 FT³) CLASS G + 3% CaCl₂
+ 1/4 LB/SK CELLO FLAKE

CEMENT TO SURFACE: YES ☒ NO ☐

ESTIMATED TOC: SURFACE

PRESSURE TEST: 1000 PSI FOR 5 MIN.

W/ 0 PSI BLEED-OFF

6 JTS. 8-5/8, 24 PPF, K-55, ST&C @ 259 FT.

TOTCO SURVEYS:

DEPTH	ANGLE
<u>679'</u>	<u>1/2°</u>
<u>1301'</u>	<u>1/2°</u>
<u>1705'</u>	<u>1/2°</u>
<u>2071'</u>	<u>3/4°</u>
<u>2458'</u>	<u>1°</u>
<u>2863'</u>	<u>1°</u>

2nd. STAGE

LEAD w/ 527 SX (1100 FT³) CLASS 'G' /LITE POZ (65/35)
+ 10% GEL + 10% SALT + 6-1/4 LB/SK GILSONITE
+ 1/4 LS/SK CELLO FLAKE + 1/4 LB/SK ANTIFOAM

TAIL W/ 132 SX (152 FT³) CLASS 'G' + 1/4 LB/SK CELLO FLAKE

CEMENT TO SURFACE: YES ☒ NO ☐

ESTIMATED TOC: Surface

DV TOOL @ 2333 FT.

1st. STAGE

LEAD w/ 100 SX (230 FT³) CLASS 'G' /LITE POZ (65/35)
+ 10% GEL + 10% SALT + 6-1/4 LB/SK GILSONITE
+ 1/4 LS/SK CELLO FLAKE + 1/4 LB/SK ANTIFOAM

TAIL W/ 90 SX (104 FT³) CLASS 'G' + 1/4 LB/SK CELLO FLAKE

CEMENT TO SURFACE: YES ☒ NO ☐

ESTIMATED TOC: 2333'

PRESSURE TEST: 2500 PSI FOR 30 MIN.

W/ No PSI BLEED-OFF

FLOAT COLLAR @ 3154 FT.

SHOE @ 3198 FT.

75 JTS. 5-1/5", 15.5 PPF, K-55, LT&C

DATE: 12-18-90

CC: P. BOWSER
B. BALE
E. BIELAMOWICZ
D. GRIFFIN