

UNITED STATES
DEPARTMENT OF INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back
to a different reservoir. Use Form 3160-3 for such proposals.)

5. Lease Designation and Serial No.

SF 078596-A

6. If Indian, Allottee or tribe Name

7. If Unit or CA, Agreement Number

8. Well Name and No.

VANDERWART A # 16

9. API Well No.

80-045-28411

10. Field and Pool, or Exploratory Area

BASIN FRUITLAND COAL GAS POOL

11. County or Parish, State

SAN JUAN County, New Mexico

1. Type of Well

GAS WELL

2. Name of Operator

QUINTANA PETROLEUM CORPORATION

3. Address and Telephone Number

(303) 692-9559

1325 So. Colorado Blvd. Suite 411 Denver, CO 80222

4. Location of Well (Sec. T., R., M., or Survey Description)

UNIT Letter B, 845' FNL & 2370' FEL

Sec. 13, T29N, R08W

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
- ☒ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☒ Casing Repair
- ☐ Altering Casing
- ☐ Other

- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Disposal Water

(Note: Report result of multiple completion on Well
Completion or Recompletion Report and Log form.)

13. Describe Proposed Completion Operations (Clearly state all pertinent details, and give pertinent dates, including estimated starting and proposed work. If well is directionally drilled
give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SUBSEQUENT REPORT OF CASING REPAIR

MOVED RIG TO LOCATION 6-6-94. KILLED WELL WITH KCL WATER. RAN BRIDGE PLUG TO 2700' AND SET.

PRESSURE TESTED BP AND CASING BELOW 1500' TO 1000 PSIG. HELD OKAY.

CONTINUED TESTING CASING AND ISOLATED FAILURE AT 37 INCHES FROM SURFACE.

CUT OFF 8-5/8" CASING AND 48" OF 4-1/2" CASING. WELDED BACK NEW SECTION OF 4-1/2"

AND NEW SECTION OF 8-5/8" CASING. RAN 1" TUBING DOWN 4-1/2" X 8-5/8" CASSING

ANNULUS AND TAGGED CEMENT AT A DEPTH OF 49'. CEMENTED CASING ANNULUS WITH CEMENT TO SURFACE.

RE-INSTALLED WELLHEAD. PRESSURE TESTED CASING STRING TO 1000 PSIG. HELD OKAY.

PRESSURE TEST WITNESSED BY NMOCD.

PLACED WELL BACK ON PRODUCTION 6-9-94.

070 FARMINGTON, NM

54 JUN 13 PM 3:01

RECEIVED
BLM

NOTE: This format is Issued in lieu of U.S. BLM Form 3160-5

14. I hereby certify that the foregoing is true and correct.

SIGNED

R. D. SIMMONS

TITLE **AGENT**

DATE: 06/13/94

(This space for Federal or State office use.)

APPROVED BY

TITLE

DATE:

CONDITIONS OF APPROVAL, IF ANY

ACCEPTED FOR RECORD

JUN 14 1994

FARMINGTON DISTRICT OFFICE

BY

NMOCD