Form 3 7-5 (Aug 7)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

BUKEAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

_	
Γ	5. Lease Serial No.
ı	NMSF078602
ı	1111101 01902
\vdash	
1	6. If Indian, Allottee or Tribe Name

abandoned we					
SUBMIT IN TRI	7. If Unit or CA/Agre	ement, Name and/or No.			
Type of Well	ner		8. Well Name and No. VANDEWART CO		
2. Name of Operator BP AMERICA PRODUCTION		ARY CORLEY Mail: corleyml@bp.com	9. API Well No. 30-045-31189-0	00-X1	
3a. Address P. O. BOX 3092 HOUSTON, TX 77253	F	b. Phone No. (include area cod Ph. 281.366.4491 x: 281.366.0700	9) 10. Field and Pool, or BASIN DAKOT		
4. Location of Well (Footage, Sec., 1	., R., M., or Survey Description)		11. County or Parish,	and State	
Sec 13 T29N R8W SESE Lot 36.43200 N Lat, 107.37400 W			SAN JUAN CO	UNTY, NM	
12. CHECK APP	ROPRIATE BOX(ES) TO I	NDICATE NATURE OF	NOTICE, REPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION	TYPE OF SUBMISSION TYPE OF ACTION				
Nation of Internal	Acidize	Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off	
□ Notice of Intent	Alter Casing	Fracture Treat	Reclamation	☐ Well Integrity	
Subsequent Report	Casing Repair	☐ New Construction	Recomplete	Other	
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporarily Abandon	Well Spud	
<u> </u>	Convert to Injection	Plug Back	☐ Water Disposal		
determined that the site is ready for APD ROW APD ROW W MIRU Drilling Unit. @ 21.45 ran 9 5/8", 32.3# H-40 surfac PPG, Yield 1.16 cuft/sx. Circ OK Drilled out CMT. Drilled a 8 3 SXS CLS G Lead mixed @ 1 Circ 40 BBLS good CMT to s Drill out CMT. Drilled a 6 1/4	final inspection.) ELL DIRECTIONALLY DRIL Hrs on 10/25/2002 Spud a 1 e CSG to 521'. CMT w/375 35 BBLS CMT to pit. NU Bi 6/4" hole to 3877'. RU & set 1.7 PPG, yield 2.63 cuft/sx 8 urface. Pressure test to 150 " hole to 8102'. TD @ 11.15	LED 3 1/2" surface hole. Drille SXS CLS G + 3% CACL2 OP & tested to 1500# high 7", 20# J-55 CSG to 385- 66 SXS 13.5 PPG, yield 0# high, 250# Low. Test 6 hrs on 11/05/2002. RU	, 0.25#/SX D29, 15.8 h, 250# low. Test 4'. CMT w/411 1.26 cuft/sx Tail. OK. & set 4 1/2",		
	Electronic Submission #15	RODUCTION ČO, sent to t sing by Adrienne Garcia o	he Farmington n 11/08/2002 (03AXG0228SE)		
Name (Printed/Typed) MARY CO	ORLEY	Title AUTH	ORIZED REPRESENTATIVE		
Signature (Electronic	Submission)	Date 11/06			
	THIS SPACE FOR	FEDERAL OR STATE	OFFICE USE		
Approved By ACCEPT	ED	ADRIEN _{Title} PETROL	NE GARCIA .EUM ENGINEER	Date 11/08/2002	
Conditions of approval, if any, are attach certify that the applicant holds legal or ea which would entitle the applicant to cond	juitable title to those rights in the s		ngton		

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Addic anal data for EC transaction #15854 that would not fit on the form

32. Additional remarks, continued

11.6#, J-55, production CSG to 8065'. CMT w/166 SXS of 9.5 PPG Litecrete CMT. Yield 2.52 Lead & 220 SXS CLS G 13.0 PPG, 1.44 cu ft yield 50/50 POZ Tail. 8 BBLs good CMT to pit. TOC 3754'.

RDMOSU Rig release @ 08.30 hrs 11/06/2002.