

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF078201-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Riddle A

9. WELL NO.

2A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND

SURVEY OR AREA
Sec. 1, T-29-N, R-9-W
N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL ☐ WELL GAS ☒ WELL OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P. O. Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1170'S, 1460'E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6426' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*05-15-75 TD 3426'. Ran 87 joints 7", 23#, K-55 intermediate casing, 3414' set at
3426'. Cemented with 339 cu. ft. cement. WOC 12 hours, held 1200#/30
minutes. Top of cement at 3050'.05-19-75 TD 5668'. Ran 55 joints 4 1/2", 10.5#, K-55 casing liner, 2391' set at
3277' to 5668'. Float collar set at 5651'. Cemented with 415 cu. ft.
cement. WOC 18 hours.10-29-75 PBTD 5650'. Tested casing to 4000#, OK. Perf'd 4678', 4692', 4703', 4720',
4738', 4761', 4791', 4816', 4828', 4836', 4852', 4894', 4980', 4988', 5005',
5030', 5115' with 1 shot per zone. Frac'd with 82,000#--20/40 sand and
87,200 gallons water. No ball drops. Flushed with 6860 gallons water.Perf'd 5223', 5245', 5290', 5312', 5324', 5346', 5364', 5374', 5387', 5388',
5389', 5390', 5405', 5422', 5458', 5476', 5515', 5578', 5596', 5617' with
1 shot per zone. Frac'd with 81,000#--20/40 sand and 84,600 gallons water.
No ball drops. Flushed with 7290 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. G. Lisco

TITLE

Drilling Clerk

DATE October 31, 1975

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NOV 5 1975