

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION


Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-		5. State Oil & Gas Lease No.
2. Name of Operator AMOCO PRODUCTION COMPANY		7. Unit Agreement Name
3. Address of Operator 501 Airport Drive, Farmington, New Mexico 87401		8. Farm or Lease Name Sammons Gas Com "D"
4. Location of Well UNIT LETTER N 130 FEET FROM THE South LINE AND 1425 FEET FROM THE West LINE, SECTION 7 TOWNSHIP 29-N RANGE 9-W NMPM.		9. Well No. 1
15. Elevation (Show whether DF, RT, GR, etc.) 5788' ungraded GL		10. Field and Pool, or Wildcat Blanco Pictured Cliffs
12. County San Juan		

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> Spud & Set Casing <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

A 12-1/4" hole was spudded in boulders on December 20, 1972, and drilled to 230'. The 8-5/8" casing was set at 219' with 200 sacks Class "A" cement with 2% CaCl₂ on December 21, 1972. The cement circulated. The hole was reduced to 7-7/8" at 219'.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed by J. ARNOLD SNELL	TITLE Area Engineer	DATE December 27, 1972
Original Signed by Emery C. Arnold	TITLE SUPERVISOR DIST. #3	DATE JAN 1 1973

CONDITIONS OF APPROVAL, IF ANY: