

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-76

APPROVED BY	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.C.S.	
LAND OFFICE	
OPERATOR	

3a. Indicate Type of Lease
State ☐ Fee ☒
3. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Firm or Lease Name Sammons Gas Com F
3. Address of Operator 2325 E. 30th Farmington, NM 87401	9. Well No. 1
4. Location of well UNIT LETTER <u>A</u> <u>790</u> FEET FROM THE <u>North</u> LINE AND <u>1070</u> FEET FROM THE <u>East</u> LINE, SECTION <u>18</u> TOWNSHIP <u>29N</u> RANGE <u>9W</u> RMPM.	10. Field and Pool, or Widom Undesignated Fruitland
15. Elevation (Show whether DF, RT, GR, etc.) 5550' GR	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPER. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	Recompletion ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moved in and rigged up service unit on 12-28-87. Set a castiron bridgeplug at 2004' and pressure tested to 3500 psi. Perforated the following intervals: 1958' - 1994', 8 jsfp, .50" in diameter, for a total of 288 holes. Fraced interval 1958' - 1994' with 60,000 gals 30# crosslinked gel and 92,000# 12-20 mesh brady sand. Set a retrievable bridgeplug at 1946' and pressure tested to 3500 psi. Perforated the following intervals: 1854' - 1874', 1910' - 1924', 4 jsfp, .50" in diameter, for a total of 136 holes. Fraced interval 1854' - 1924' with 111,000 gals 30# crosslinked gel and 200,000# 12-20 mesh brady sand. Retrieved bridgeplug set at 1946'. Landed 1-1/4" tubing and released the rig on 1-20-88.

RECEIVED
FEB 02 1988
OIL CON. DIV.
DIST 2

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed BS Shaw TITLE Adm. Supervisor DATE 1-25-88

Original Signed by FRANK T. CHAVEZ

SUPERVISOR DISTRICT ☒

FEB 02 1988